



МОНИТОРЫ БИЗНЕС И  
ПРОДУКТИВНОСТЬ

PRO MP242PMG

PRO MP242PMG


## Business & Productivity Monitor



Picture and logos

### SELLING POINTS

- Встроенная FHD веб-камера с цифровым микрофоном и защитой камеры.
- Дисплей с сертификацией TÜV для защиты здоровья глаз.
- Технология MSI EyesErgo с анти-мерцанием помогает предотвратить усталость и напряжение глаз.
- Частота обновления 120 Гц обеспечивает лучший просмотр с изображением без мерцания.
- MSI Eye-Q Check помогает следить за состоянием глаз и напоминает о перерывах при длительном использовании монитора.
- Подставка с эргономичными функциями: наклон, поворот, регулировка высоты и ориентации.
- Регулируемая подставка с возможностью установки мини-ПК для улучшенной эргономики и аккуратной организации рабочего места.
- Стандартное крепление VESA и слот для аксессуаров.
- Два встроенных динамика.



1. 5-позиционный навигационный джойстик
2. AC-in
3. 1x выход для наушников
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@120Гц)
6. 1x D-Sub (VGA)
7. 2x USB 2.0 Type-A
8. 1x USB 2.0 Type-B
9. Замок Kensington



МОНИТОРЫ БИЗНЕС И

ПРОДУКТИВНОСТЬ

## PRO MP242PMG

PRO MP242PMG

## SPECIFICATION

Model	Part No	9S6-3PD89T-005
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	47.11~144.23 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/80%
	NTSC (CIE1931 area percentage/overlap)	79%/72%
	SRGB (CIE1976 area percentage/overlap)	115%/99%
	SRGB (CIE1931 area percentage/overlap)	111%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	82%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	91%/89%
	DCI-P3 (CIE1931 area percentage/overlap)	82%/81%
	Rec.709 (CIE1976 area percentage/overlap)	115%/99%
	Rec.709 (CIE1931 area percentage/overlap)	111%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	67%/67%
	Rec.2020 (CIE1931 area percentage/overlap)	59%/59%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	12M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



МОНИТОРЫ БИЗНЕС И

ПРОДУКТИВНОСТЬ

## PRO MP242PMG

## PRO MP242PMG

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
	Adjustment (Tilt)	-5° ~ 20°
Design	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
	Product Dimension with Stand (WxDxH) (mm)	612 x 227 x 429
Dimension & Weight (product)	Product Dimension without Stand (WxDxH) (mm)	612 x 54 x 376
	Stand Dimension (WxDxH) (mm)	260 x 227 x 412
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
	Inside Carton Dimension (WxDxH) (cm)	60 x 14 x 41
Dimension & Weight (box)	Outer Carton Dimension (WxDxH) (cm)	61.5 x 15.5 x 43.3
	Weight (Gross kg)	TBD
	Barcode Info	EAN
		4711377260404