



## Thermal Receipt Printer

### XP-E200L / E260L




- Horizontal, Wall-hanging design.
- OPOS driver available for all interface
- QR code supported



# XP-E200L / E260L

## Thermal Receipt Printer



| MODEL                  | XP-E200L   | XP-E260L       |
|------------------------|--|----------------|
| Printing method        | Direct thermal   |                |
| Printing speed         | 230mm/s  | 260mm/s        |
| Paper width            | 79.5 ± 0.5mm   |                |
| Printable area         | 72mm(adjustable by commands)   |                |
| Maximum paper diameter | Φ80 mm   |                |
| Paper thickness        | 0.06-0.08mm  |                |
| Column capacity        | 576 dots/line(adjustable by commands)  |                |
| Line space             | 3.75mm(Changeable by commands)   |                |
| Commands               | Compatible with ESC/POS  |                |
| Interface type         | USB+Serial / Lan   | USB+Serial+Lan |
| Character size         | ANK, Font A: 12×24 dots<br>Font B: 9×17 dots<br>simplified/traditional Chinese: 24x24 dots   |                |
| Dimension              | 192×140×140 mm (D×W×H)   |                |
| Gross weight           | 1.12 kg  |                |
| Bar code               | UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128   |                |
| 2-dimension code       | QR CODE(default) / PDF417(alternative)   |                |
| Code page              | PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251) |                |
| Cutter                 | Partial  |                |
| Cutter life            | 1.5 million cuts   |                |
| Print head life        | 100KM  |                |
| Input buffer           | 64 Kbytes  |                |
| NV Flash               | 256 Kbytes   |                |
| Power adaptor          | AC110V/220V, 50~60Hz   |                |
| Power source           | DC 24V/2.5A  |                |
| Cash drawer output     | DC 24V/1A  |                |
| Work environment       | Temperature: 0~45°C , humidity: 10~80RH%   |                |
| Storage environment    | Temperature: -10~60°C , humidity: 10~90RH%   |                |
| Operating system       | Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux   |                |



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
[Http://www.xprintertech.com](http://www.xprintertech.com)  
Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

