

Все для гейминга



Picture and logos

SELLING POINTS

- IPS-панель с великолепным качеством изображения: точная цветопередача и высокая яркость
- Формат UWQHD: высокое разрешение 3440x1440 обеспечивает четкое и детализированное изображение
- Повышенная частота обновления экрана: 155Гц
- Низкое время отклика ЖК-матрицы: 1 мс
- Wide Color Gamut: Широкий цветовой охват: реалистичное отображение каждого оттенка
- Эффективная многозадачность: соотношение сторон 21:9, вывод изображения с двух источников сигнала, функция KVM-переключателя.
- Режим Night Vision: «ночное зрение» для улучшенной ориентации в темных игровых сценах
- Тонкая экранная рамка: ничто не отвлекает взгляд от изображения
- Комфорт для пользователя: подавление мерцания экрана и снижение интенсивности синего света - технологии Anti-Flicker и Less Blue Light
- Широкие углы обзора: 178°



1. 5-позиционный навигационный джойстик
2. AC Power Jack
3. Headphone Out
4. HDMI™ (2.0b) x 2
5. DisplayPort (1.4a)
6. USD Type-C (DP alt)
7. USB 2.0 Type-B
8. USB 2.0 Type-A x 2



М О Н И Т О Р Ы
MAG401QR
MAG401QR

SPECIFICATION

Model	Entity MKT Name	MAG401QR
	Part No	9S6-3EA54H-016
	Color	ID1/Black-Black
Display	Screen Size	40" (101.6 cm)
	Active Display Area (mm)	926.22(H)x387.72(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	3440x1440 (UWQHD)
	Pixel pitch (mm)	0.2697(H)x0.2697(V)
	Aspect Ratio	21:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~155Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	400
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~160 KHz(H) / 60~144 Hz(V)
	Refresh Rate	155Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	103%/86%
	NTSC (CIE1931 area percentage/overlap)	88%/81%
	sRGB (CIE1976 area percentage/overlap)	118%/99%
	sRGB (CIE1931 area percentage/overlap)	124%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	101%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	92%/82%
	DCI-P3 (CIE1976 area percentage/overlap)	95%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	91%/91%
	Rec.709 (CIE1976 area percentage/overlap)	118%/99%
	Rec.709 (CIE1931 area percentage/overlap)	124%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	65%/65%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0
	HDMI HDCP version	2.2
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.2
Warranty	Warranty	12M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	39
	Annual Energy Consumption (KWh)	39
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



МОНИТОРЫ

MAG401QR

MAG401QR

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	945.22 x 289.63 x 530.29
	Product Dimension without Stand (WxDxH) (mm)	945.22 x 83.32 x 416.12
	Stand Dimension (WxDxH) (mm)	672.42 x 289.63 x 386.56
	Weight (Net kg)	10.3
	Weight Without Stand (kg)	8
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	116.7 x 16 x 51.5
	Outer Carton Dimension (WxDxH) (cm)	118.2 x 17.3 x 53.7
	Weight (Gross kg)	12.4
Barcode Info	EAN	4711377080514