

Technical Data Sheet

Favorit MГE-46B



Packages:
20L, 60L, 208L

[EN] **Favorit MГE-46B** hydraulic oil based on minerals, designed for hydraulic systems (hydrostatic drive) of agricultural, road-building and other special equipment. It contains an effective complex of additives providing a high level and stability of antiwear and antioxidant properties.

[RU] **Favorit MГE-46B** масло гидравлическое на минеральной основе, предназначенное для гидравлических систем (гидростатического привода) сельскохозяйственной, строительно-дорожной и другой специальной техники. Содержит эффективный комплекс присадок, обеспечивающий высокий уровень и стабильность противоизносных и антиокислительных свойств.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	44,22
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	
Viscosity index	STB 1797	94,8
Flash poin, °C	GOST 4333	220
Pour point, °C	GOST 20287	
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m ³	GOST 3900	870

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.