

Product information

megol Motorenoel High Condition SAE 5W-40



Description

Premium low-friction motor oil for year-round use. Developed for modern injection engines with and without turbocharger. Its combination of unconventional hydrocrack-based base oils with the very latest additive technology guarantees low viscosity and high shear resistance. The perfectly tailored formulation prevents deposits, lowers friction losses and provides optimum protection for the engine against wear. This delivers fuel savings while prolonging the life of the engine, among other benefits.

Range of applications: Passenger cars

SAPS level: High-SAPS

Follow the manufacturer's instructions!

Specifications and approvals:

ACEA A3 • ACEA B4 • API CF • API SN • MB-Approval 229.5
• Porsche A40 • VW 502 00 • VW 505 00

Meguin also recommends this product for vehicles that are subject to the following specifications:

BMW Longlife-01 (until my 2018) • Fiat 9.55535-H2 • Fiat 9.55535-M2 • Opel GM-LL-B-025 • Peugeot Citroen (PSA) B71 2294 • Peugeot Citroen (PSA) B71 2296 • Renault RN 0710 • Renault RN 0700

Characteristic data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	80,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,0 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	<= 60000 mPas ASTM D4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	232 °C DIN ISO 2592



Characteristic data

Total base number	11,3 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	Part no. 3199 D-GB-F-RUS-GR-ARAB
5 l Canister plastic	Part no. 3198 D-GB-F-RUS-GR-ARAB
20 l Bucket plastic	Part no. 9484 D-GB
60 l Drum sheet metal	Part no. 9485 D-GB
200 l Drum sheet metal	Part no. 9486 D-GB
1 l Bulk goods	Part no. 9457 D-GB