



PHAROS

For TP-Link Pharos Series Products

User Guide

1910012245 REV3.0.0

August 2017

CONTENTS

About This Guide	1
Chapter 1 Overview	2
Introduction	2
System Requirements	2
Getting Started	2
Navigation.....	4
Chapter 2 Operation Modes	6
Access Point	6
Client	7
Repeater (Range Extender)	8
Bridge.....	8
AP Router	9
AP Client Router (WISP Client).....	9
Chapter 3 Quick Setup Guide.....	11
Access Point	11
Client	13
Repeater (Range Extender)	16
Bridge.....	19
AP Router	23
AP Client Router (WISP Client).....	27
Chapter 4 Status Tab	33
Status Information	34
Monitor	38
Chapter 5 Network Tab	43
WAN	44
LAN	50
Management VLAN	54
Forwarding	54
Security.....	59

Access Control	62
Static Routing	63
Bandwidth Control	64
IP&MAC Binding	65
Chapter 6 Wireless Tab	67
Wireless Basic Settings	68
Wireless Client Settings.....	70
Wireless AP Settings	71
Multi-SSID	77
Wireless MAC Filtering	78
Wireless Advanced Settings	79
Chapter 7 Management Tab	82
System Log	83
Miscellaneous.....	84
Ping Watch Dog.....	85
Dynamic DNS.....	86
Web Server	87
SNMP Agent	88
SSH Server.....	90
RSSI LED Thresholds.....	90
Chapter 8 System Tab	92
Device	93
Location.....	93
User Account.....	93
Time Setting	94
Firmware Update.....	96
Configuration.....	97
Chapter 9 Tools List.....	99
Ping.....	99
Traceroute.....	100
Speed Test.....	100

Survey.....	102
Spectrum Analysis.....	103
Appendix A: Pharos MAXtream TDMA.....	104
Appendix B: Glossary.....	105

About This Guide

This User Guide contains information for setup and management of TP-Link Pharos series products. Please read this guide carefully before operation.

When using this guide, please notice that features of the product may vary slightly depending on the model and software version you have, and on your location, language, and Internet service provider. All screenshots, images, parameters and descriptions documented in this guide are used for demonstration only.

Some models featured in this guide may be unavailable in your country or region. For local sales information, visit <http://www.tp-link.com>.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute the warranty of any kind, express or implied. Users must take full responsibility for their application of any products.

More Info

The latest software, management app and utility can be found at [Download Center](http://www.tp-link.com/support) at <http://www.tp-link.com/support>.

The Installation Guide can be found where you find this guide or inside the package of the product.

Specifications can be found on the product page at <http://www.tp-link.com>.

A Technical Support Forum is provided for you to discuss our products at <http://forum.tp-link.com>.

Our Technical Support contact information can be found at the [Contact Technical Support](http://www.tp-link.com/support) page at <http://www.tp-link.com/support>.

Chapter 1 Overview

Introduction

PHAROS is TP-Link's next generation outdoor product series dedicated to long-distance outdoor wireless networking solutions.

PHAROS is a powerful Web-based operating system, which is integrated into all Pharos series products.

New features of Pharos series products are listed as follows:

- Provides User-friendly UI design.
- TP-Link Pharos MAXstream (Time-Division-Multiple-Access) technology improves product performance in throughput, capacity and latency, which are ideal for Point-to-multipoint applications.
- Supports multiple operation modes: Access Point, Client, Repeater (Range Extender), Bridge, AP Router and AP Client Router (WISP Client).
- Provides system-level optimization for long-distance wireless transmission.
- Supports selectable bandwidth of 5/10/20/40MHz.
- Supports easy antenna alignment with Wireless Signal Indicators on Web interface.
- Provides Throughput Monitor, Spectrum Analyzer, Speed Test and Ping tools.
- Supports discovery and management via Pharos Control application.

System Requirements

- Operating system:
Microsoft Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10, Linux, or Mac OS X
- Web Browser:
Google Chrome, Safari, Firefox, and Apple Safari. IE browsers are not recommended.

Getting Started

To access the PharOS Configuration Interface, perform the following steps:

1. Configure the Ethernet adapter on your computer with a static IP address on the 192.168.0.x subnet (for example, IP address: 192.168.0.100 and subnet mask: 255.255.255.0).
2. Launch your Web browser. Enter the default IP address of your device in the address field. Press **Enter** (PC) or **Return** (Mac).

For Example, enter 192.168.0.254 to access the PharOS.



3. Upon initial login, enter **admin** in the *Username* and *Password* fields, and select the appropriate language from the *Language* drop-down lists. Check the box next to *I agree to these terms of use*, and click **Login**.

 A screenshot of the TP-Link login page. The page title is "Login". It features the TP-Link logo on the left. On the right, there are three input fields: "User Name" with "admin" entered, "Password" (empty), and "Language" with "English" selected in a dropdown menu. Below the fields is a "TERMS OF USE" section with a text box containing legal disclaimer text. At the bottom left, there is a checkbox labeled "I agree to these terms of use". At the bottom right, there are two buttons: "Login" and "Clear".

4. We recommend you change the device's user name and password from its default settings for network security. Enter and confirm new user name and password, then click **Finish**.

 A screenshot of the TP-Link "Change Password" page. The page title is "Change Password". It features the TP-Link logo on the left. On the right, there are three input fields: "New User Name", "New Password", and "Confirm Password". Below the fields is a "TERMS OF USE" section with a text box containing the text: "It is recommended to change the device user name and password from its default settings." At the bottom right, there are two buttons: "Finish" and "Clear".

5. For subsequent logins, you only need to enter the user name and password that you have set to log in.

 A screenshot of the TP-Link login page for subsequent logins. The page title is "Login". It features the TP-Link logo on the left. On the right, there are two input fields: "User Name" and "Password". Below the fields is a "TERMS OF USE" section with a text box containing legal disclaimer text. At the bottom right, there are two buttons: "Login" and "Clear".

Navigation

The PharOS Web Interface contains six main tabs, each of which provides a Web-based management page to configure the specific parameters of the Pharos series products.

The screenshot shows the TP-Link PharOS web interface. At the top, there is a navigation bar with the following tabs: QUICK SETUP, STATUS (selected), NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. The main content area is divided into several sections:

- Device Information:**
 - Device Name: CPE520
 - Device Model: CPE520 v2.0
 - Firmware Version: 2.0.0 Build 20160908 Rel. 36610 (5553)
 - System Time: 2015-01-01 00:27:03
 - Uptime: 0 days 00:27:05
 - CPU: 2% (indicated by a progress bar)
 - Memory: 52% (indicated by a progress bar)
- Wireless Settings:**
 - MAXtream: OFF
 - Channel/Frequency: 44 / 5220MHz
 - Channel Width: 20/40MHz
 - IEEE802.11 Mode: A/N Mixed
 - Max TX Rate: 300.0Mbps
 - Transmit Power: 3dBm
 - Distance: 0.0km
- Wireless Signal Quality:**
 - Signal Strength: N/A
 - Noise Strength: N/A
 - SNR: N/A
 - Transmit CQ: 100 (indicated by a progress bar)
- Radio Status:**
 - AP: Enabled
 - MAC Address: 98-DE-D0-88-6C-84
 - SSID: TP-LINK_Outdoor_886C84
 - Security Mode: None
 - Connected Stations: 0
- LAN:**
 - MAC Address: 98-DE-D0-88-6C-84

- **Quick Setup**

On **Quick Setup Guide**, you can quickly configure your device through the step-by-step Quick Setup Wizard.

- **Status**

The **Status Tab** displays a summary of the link status information, current values of the basic configuration settings (depending on the operating mode), network settings and information, and traffic statistics.

- **Network**

The **Network Tab** configures the function of WAN, LAN, Management VLAN, forwarding, security, access control, static routing, bandwidth control and IP&MAC binding.

- **Wireless**

On The **Wireless Tab**, you can configure the related wireless parameters in different modes.

- **Management**

The **Management Tab** configures system management services: System Log, Miscellaneous, Ping Watch Dog, and Dynamic Domain Name System (DDNS). Web server, Simple Network Management Protocol (SNMP), SSH server, RSSI LED Thresholds are also available.

- **System**

The **System Tab** controls system maintenance routines, device customization, location management, user account management, firmware update, Time setting and configuration backup.

- **Tools**

The **Tools list** provides some useful tools including Ping, Traceroute, Speed Test, Survey and Spectrum Analysis.

Chapter 2 Operation Modes

The Pharos series products support six modes to satisfy user's diversified network requirements including Access Point mode, Client mode, Repeater (Range Extender) mode, Bridge mode, AP Router mode and AP Client Router (WISP Client) mode. This chapter introduces typical usage scenarios of each mode. You can choose the desired scenario according to your needs, and refer to the Installation Guide for hardware connection instruction and **Chapter 3 Quick Setup Guide** for software configuration.

Access Point

In AP mode, the device acts as a central hub and provides wireless access point for wireless clients, thus the AP mode is very applicable to the following three scenarios. Meanwhile, Multi-SSID function can be enabled in this mode, providing up to four wireless networks with different SSIDs and passwords.


- **Scenario 1**

Network requirements: Establish the network coverage in the remote areas without long-distance cabling.

The device in the network: In the adjacent town covered by wired network, ISP (Internet Service Provider) can put up a device in AP mode with the access to ISP network by connecting to ISP's router to transform wired signal into wireless one. The remote users can put up a device in AP Client Router mode to access the Internet the AP device provides wirelessly.

Advantages: Transmit data wirelessly across a long distance and reduce the cabling cost.

Network diagram:




- **Scenario 2**

Network requirements: Combine two separate office networks as one.

The device in the network: Two devices in AP and Client mode respectively connect to the switches in two office networks so as to connect two office networks.

Advantages: Establish a point-to-point WLAN across a long distance to achieve the connectivity between two networks and avoid the cabling trouble.

Network diagram:




- **Scenario 3**

Network requirements: Establish wireless network coverage in the campus, community, industrial park or public places to provide wireless access points for wireless users.

The device in the network: With the access to campus wired network or other wired local area networks, the device in AP mode provides the wireless access point based on the existing wired network for wireless clients, such as smart phones, laptops and tablets.

Advantages: Increase wireless access points and enrich the access ways of local area network.

Network diagram:




Client

Network requirements: The most common usage scenario of Client is point-to-point networking with AP for combining two separate office networks. Please refer to **Scenario 2 of Access Point** for detailed information.

The device in the network: In this mode, the device actually serves as a wireless adapter to receive the wireless signal from root AP or Station. In the case, wired devices can access the network provided by root AP or Station through connecting to Client.

Network diagram:




Repeater (Range Extender)

The device in Repeater mode can extend wireless coverage of an existing wireless network. The SSID and encryption type of the device should be the same as those of root AP.

Network requirements: Repeat wireless signal.

The device in the network: If you want to combine two networks via wireless connection but the distance is beyond the networks' wireless coverage range, you can put one or more devices in Repeater mode along the path to repeat the wireless signal and extend the wireless transmission range.

Network diagram:




Bridge

Network requirements: Reinforce the wireless signal strength of the root AP device to eliminate the wireless signal-blind areas. Meanwhile, the wireless users can use the SSID and encryption type different from those of the root AP device to access the network.

The device in the network: Similar to the Repeater mode, the Bridge mode is used to reinforce the exiting wireless signal. However, the very difference is that the Bridge has its own SSID and encryption type different from those of root AP.

Network diagram:



AP Router

Network requirements: Establish the wireless network coverage in the campus, community, industrial park or other public places and so on.

The device in the network: Similar to the home wireless router, the device in AP Router mode connects to root ADSL/Cable Modem. The difference lies in that the coverage area of this device is wider. Smart phones, laptops, and other wireless clients can share wide area network via the access to wireless network this device provides.

Network diagram:




NOTE:

In this mode, the device cannot be managed through the port connected to ADSL/Cable Modem. To manage the device, you can connect the management host to the device wirelessly or via the other LAN port.

AP Client Router (WISP Client)

In AP Client Router mode, after accessing the wireless network provided by WISP, the device provides wireless network service for downstream wireless clients. Meanwhile, the device allows wired devices, such as desktop computer, to access it via LAN1 port or PoE adapter’s LAN port. In this way, all members of a home user can share the Internet using one account applied from WISP.

WISP



WISP's network

AP Client Router
LAN: 192.168.0.254
WAN: Dynamic IP



User Network



Chapter 3 Quick Setup Guide

Quick Setup wizard allows you to quickly configure your device step by step. Choose the suitable operation mode according to your network environment and follow the step-by-step instructions.

tp-link PHAROS

Operation Mode: Access Point

Tools

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

Operation Mode

Please select the proper operation mode according to your needs:

- Access Point In this mode, the AP will act as a central hub for different wireless LAN clients. Multi-SSID is also available in this mode, which supports up to 4 different SSIDs and passwords.
- Client In client mode, the device can connect to a wired device and work as a wireless adapter to receive wireless signals from your wireless network.
- Repeater In this mode, the device can copy and reinforce the existing wireless signal to extend the coverage of the signal, especially for a large space to eliminate signal-blind corners.
- Bridge Bridge mode borrows existing wireless internet and broadcasts it using a different SSID and password. In this mode, you can set up a wireless client to connect with a root AP and a wireless AP for local wireless coverage.
- AP Router In this mode, the device enables multiple users to share the internet. The wireless ports share the same IP address as the Ethernet WAN port to connect to the ISP. The wireless port can be regarded as a LAN port while in AP Router mode.
- AP Client Router (WISP Client) In this mode, multiple users can share an internet connection provided by a WISP. The LAN port devices share the same IP as that assigned by the WISP to the Wireless port. While connected to a WISP, the wireless port works as a WAN port in AP Client Router mode. The Ethernet port acts as a LAN port.

Next

Access Point

If **Access Point** is selected, click **Next** and take the following steps:

1. The **LAN Settings** page will appear as shown below. The default **IP Address** is 192.168.0.254 and the default **Subnet Mask** is 255.255.255.0. You can change the IP Address and Subnet Mask on this page when there is an IP conflict with other devices. Click **Next**.

The screenshot shows the 'LAN Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP, STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. The 'QUICK SETUP' tab is active. Below the navigation bar, the page title is 'LAN Settings'. There are two input fields: 'IP Address' with the value '192.168.0.254' and 'Subnet Mask' with the value '255.255.255.0'. At the bottom of the page, there are two buttons: 'Back' and 'Next'.

2. The **Wireless AP Settings** page will appear as shown below. Create an easy-to-remember name for your wireless network. We recommend to select **WPA-PSK/WPA2-PSK** in the **Security** box and enter the PSK Password below to prevent unauthorized access to your AP. Enter the distance between this device and the furthest client in **Distance Setting**. Then click **Next**.

The screenshot shows the 'Wireless AP Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP, STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. The 'WIRELESS' tab is active. Below the navigation bar, the page title is 'Wireless AP Settings'. There are several settings: 'SSID' with the value 'TP-LINK_Outdoor_BD205C', 'Mode' with a dropdown menu showing '802.11a/n', 'Channel Width' with a dropdown menu showing '20/40MHz', 'Channel/Frequency' with a dropdown menu showing 'Auto', and 'Security' with a dropdown menu showing 'None'. Below these is a 'PSK Password' input field with a 'Show' checkbox. A note below the password field reads: 'We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.' Below the note is a 'Distance Setting' input field with the value '0' and a range '(0-27.9)km'. At the bottom, there is a 'MAXtream' checkbox with the label 'Enable' and a help icon. At the bottom of the page, there are two buttons: 'Back' and 'Next'.

- The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

Finish

Operation Mode: Access Point

IP Address: 192.168.0.254

Subnet Mask: 255.255.255.0

SSID: TP-LINK_Outdoor_BD205C

Mode: 802.11a/n

Channel Width: 20/40MHz

Channel/Frequency: Auto

Security: None

Distance Setting: 0 km

MAXtream: Disable

Back Finish

Client

If **Client** is selected, click **Next** and take the following steps:

- The **LAN Settings** page will appear as shown below. The default **IP Address** is 192.168.0.254 and the default **Subnet Mask** is 255.255.255.0. You can change the IP Address and Subnet Mask on this page when there is an IP conflict with other devices. We recommend you keep it by default. Click **Next**.

The screenshot shows the 'LAN Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'LAN Settings'. There are two input fields: 'IP Address' with the value '192.168.0.254' and 'Subnet Mask' with the value '255.255.255.0'. At the bottom of the page, there are two buttons: 'Back' and 'Next'.

2. The **Wireless Client Settings** page will appear as shown below. Click **Survey** to search for wireless networks.

The screenshot shows the 'Wireless Client Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS (selected), MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'Wireless Client Settings'. There are several input fields and a button: 'SSID of Remote AP' (empty), 'Survey' (button), 'MAC of Remote AP' (empty), 'Lock to AP' (checkbox), 'Mode' (dropdown menu, value: 802.11a/n), 'WDS' (dropdown menu, value: Auto), 'Channel Width' (dropdown menu, value: 20/40MHz), 'Security' (dropdown menu, value: None), 'PSK Password' (empty), 'Show' (checkbox), and 'Distance Setting' (input field, value: 0, range: (0-27.9)km). A note below the PSK Password field reads: 'We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.' At the bottom of the page, there are two buttons: 'Back' and 'Next'.

3. The AP list will appear as shown below. Select the desired wireless network and click **Connect**. It's possible that two or more networks use the same SSID in the AP list. **Lock to AP** can make the device connect to the specified AP you had connected before the next time.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
-------------	--------	---------	----------	------------	--------

Wireless Client Settings

<input type="checkbox"/>	BSSID	SSID	MAXstream	Device Name	SNR (dB)	Signal / Noise (dBm)	Channel	Security
<input type="checkbox"/>	18-A6-F7-41-26-46	daisy 3	No		42	-53/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-27-7F-6E	SR20_5G	No		50	-45/-95	5220 (44)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-17-A6-E3	EAP-Show	No		14	-81/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	D4-61-FE-5A-2A-00	das	No		11	-85/-96	5180 (36)	WPA-PSK/WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-54-DB	deco	No		35	-61/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-1F	deco	No		30	-66/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-74	deco	No		47	-49/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-54-DB		No		37	-59/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-1F		No		31	-65/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-74		No		47	-49/-96	5200 (40)	WPA2-PSK

4. If the root AP needs password to be connected, you should select the same **Mode**, **Channel Width** and **Security** type and enter the same **PSK Password** as entered on the root AP/router. Enter the distance between this device and the root AP in **Distance** setting. Then click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
-------------	--------	---------	----------	------------	--------

Wireless Client Settings

SSID of Remote AP:

MAC of Remote AP: Lock to AP

Mode:

WDS:

Channel Width:

Security:

PSK Password: Show

We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.

Distance Setting: (0-27.9)km

- The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

Finish

Operation Mode: Client

LAN IP Address: 192.168.0.254

LAN Subnet Mask: 255.255.255.0

SSID of Remote AP: TP-LINK_DC91_5G

Mode: 802.11a/n

WDS: Auto

Channel Width: 20/40MHz

Security: WPA-PSK / WPA2-PSK

Distance Setting: 0 km

Back Finish

Repeater (Range Extender)

If **Repeater (Range Extender)** is selected, click **Next** and take the following steps:

- The **LAN Settings** page will appear as shown below. The default **IP Address** is 192.168.0.254 and the default **Subnet Mask** is 255.255.255.0. You can change the IP Address and Subnet Mask on this page when there is an IP conflict with other devices. We recommend you keep it by default. Click **Next**.

The screenshot shows the 'LAN Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'LAN Settings'. There are two input fields: 'IP Address' with the value '192.168.0.254' and 'Subnet Mask' with the value '255.255.255.0'. At the bottom of the page, there are two buttons: 'Back' and 'Next'.

- The **Wireless Client Settings** page will appear as shown below. Click **Survey** to search for wireless networks.

The screenshot shows the 'Wireless Client Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP, STATUS, NETWORK, WIRELESS (selected), MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'Wireless Client Settings'. There are several input fields and a button: 'SSID of Remote AP' (empty), 'Survey' button, 'MAC of Remote AP' (empty), 'Lock to AP' checkbox (unchecked), 'Mode' dropdown menu (selected '802.11a/n'), 'WDS' dropdown menu (selected 'Auto'), 'Channel Width' dropdown menu (selected '20/40MHz'), 'Security' dropdown menu (selected 'None'), 'PSK Password' (empty), 'Show' checkbox (unchecked), and 'Distance Setting' (value '0', range '(0-27.9)km'). A note below the PSK Password field reads: 'We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.' At the bottom of the page, there are two buttons: 'Back' and 'Next'.

- The AP list will appear as shown below. Select the desired wireless network and click **Connect**. It's possible that two or more networks use the same SSID in the AP list. **Lock to AP** can make the device connect to the specified AP you had connected before the next time.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM			
Wireless Client Settings								
<input type="checkbox"/>	BSSID	SSID	MAXstream	Device Name	SNR (dB)	Signal / Noise (dBm)	Channel	Security
<input type="checkbox"/>	18-A6-F7-41-26-46	daisy 3	No		42	-53/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-27-7F-6E	SR20_5G	No		50	-45/-95	5220 (44)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-17-A6-E3	EAP-Show	No		14	-81/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	D4-61-FE-5A-2A-00	das	No		11	-85/-96	5180 (36)	WPA-PSK/WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-54-DB	deco	No		35	-61/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-1F	deco	No		30	-66/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-74	deco	No		47	-49/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-54-DB		No		37	-59/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-1F		No		31	-65/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-74		No		47	-49/-96	5200 (40)	WPA2-PSK
WPA-PSK/WPA2								
<input type="button" value="Back"/> <input type="button" value="Refresh"/> <input type="button" value="Connect"/> <input type="button" value="Lock to AP"/>								

4. If the root AP needs password to be connected, you should select the same **Mode**, **Channel Width** and **Security** type and enter the same **PSK Password** as entered on the root AP/router. Enter the distance between this device and the root AP/router in **Distance setting**. Then click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless Client Settings					
SSID of Remote AP:		<input type="text" value="7200_5G"/>	<input type="button" value="Survey"/>		
MAC of Remote AP:		<input type="text" value="50-C7-BF-01-88-1F"/>	<input type="checkbox"/> Lock to AP		
Mode:		<input type="text" value="802.11a/n"/>			
WDS:		<input type="text" value="Auto"/>			
Channel Width:		<input type="text" value="20/40MHz"/>			
Security:		<input type="text" value="WPA-PSK / WPA2-PSK"/>			
PSK Password:		<input type="password" value="*****"/>	<input type="checkbox"/> Show		
We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.					
Distance Setting:		<input type="text" value="0"/>	(0-27.9)km		
<input type="button" value="Back"/> <input type="button" value="Next"/>					

5. The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

Finish

Operation Mode: Repeater

IP Address: 192.168.0.254

Subnet Mask: 255.255.255.0

SSID of Remote AP: 7200_5G

Mode: 802.11a/n

WDS: Disable

Channel Width: 20/40MHz

Security: WPA-PSK / WPA2-PSK

Distance Setting: 0 km

Back Finish

Bridge

If **Bridge** is selected, click **Next** and take the following steps:

1. The **LAN Settings** page will appear as shown below. The default **IP Address** is 192.168.0.254 and the default **Subnet Mask** is 255.255.255.0. You can change the IP Address and Subnet Mask on this page when there is an IP conflict with other devices. We recommend you keep it by default. Click **Next**.

The screenshot shows the 'LAN Settings' page within a navigation menu. The menu includes 'QUICK SETUP', 'STATUS', 'NETWORK', 'WIRELESS', 'MANAGEMENT', and 'SYSTEM'. The 'QUICK SETUP' tab is active. Below the title 'LAN Settings', there are two input fields: 'IP Address' with the value '192.168.0.254' and 'Subnet Mask' with the value '255.255.255.0'. At the bottom of the page, there are two buttons: 'Back' and 'Next'.

2. The **Wireless Client Settings** page will appear as shown below. Click **Survey** to search for wireless networks.

The screenshot shows the 'Wireless Client Settings' page within the same navigation menu. The 'WIRELESS' tab is active. Below the title 'Wireless Client Settings', there are several configuration options:

- 'SSID of Remote AP': An empty text input field.
- 'MAC of Remote AP': An empty text input field.
- 'Mode': A dropdown menu set to '802.11a/n'.
- 'WDS': A dropdown menu set to 'Auto'.
- 'Channel Width': A dropdown menu set to '20/40MHz'.
- 'Security': A dropdown menu set to 'None'.
- 'PSK Password': An empty text input field with a 'Show' checkbox to its right.
- 'Distance Setting': A text input field with the value '0' and a range '(0-27.9)km' to its right.

 A 'Survey' button is located to the right of the SSID field. Below the PSK Password field, there is a note: 'We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.' At the bottom of the page, there are two buttons: 'Back' and 'Next'.

3. The AP list will appear as shown below. Select the desired wireless network and click **Connect**. It's possible that two or more networks use the same SSID in the AP list. **Lock to AP** can make the device connect to the specified AP you had connected before the next time.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM			
Wireless Client Settings								
<input type="checkbox"/>	BSSID	SSID	MAXtream	Device Name	SNR (dB)	Signal / Noise (dBm)	Channel	Security
<input type="checkbox"/>	18-A6-F7-41-26-46	daisy 3	No		42	-53/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-27-7F-6E	SR20_5G	No		50	-45/-95	5220 (44)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-17-A6-E3	EAP-Show	No		14	-81/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	D4-61-FE-5A-2A-00	das	No		11	-85/-96	5180 (36)	WPA-PSK/WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-54-DB	deco	No		35	-61/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-1F	deco	No		30	-66/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-74	deco	No		47	-49/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-54-DB		No		37	-59/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-1F		No		31	-65/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-74		No		47	-49/-96	5200 (40)	WPA2-PSK
WPA-PSK/WPA2								
<input type="button" value="Back"/> <input type="button" value="Refresh"/> <input type="button" value="Connect"/> <input type="button" value="Lock to AP"/>								

4. If the root AP needs password to be connected, you should select the same **Mode**, **Channel Width** and **Security** type and enter the same *PSK Password* as entered on the root AP. Enter the distance between this device and the root AP/router in *Distance setting*. Then click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless Client Settings					
SSID of Remote AP:		<input type="text" value="7200_5G"/>	<input type="button" value="Survey"/>		
MAC of Remote AP:		<input type="text" value="50-C7-BF-01-88-1F"/>	<input type="checkbox"/> Lock to AP		
Mode:		<input type="text" value="802.11a/n"/>			
WDS:		<input type="text" value="Auto"/>			
Channel Width:		<input type="text" value="20/40MHz"/>			
Security:		<input type="text" value="WPA-PSK / WPA2-PSK"/>			
PSK Password:		<input type="text" value="*****"/>	<input type="checkbox"/> Show		
<p>We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.</p>					
Distance Setting:		<input type="text" value="0"/>	(0-27.9)km		
<input type="button" value="Back"/> <input type="button" value="Next"/>					

5. Create a new **SSID** and **PSK password** for the local wireless network. The wireless AP settings for the local network will be set the same as your root AP by default. Click **Next**.

The screenshot shows the 'Wireless AP Settings' page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'Wireless AP Settings'. The settings are as follows:

- Wireless Radio: Enable
- SSID: TP-LINK_Outdoor_BD205C
- Security: WPA-PSK / WPA2-PSK (dropdown menu)
- PSK Password: [masked with dots] Show

Below the settings, there is a note: "We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode." At the bottom of the page, there are two buttons: 'Back' and 'Next'.

6. The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

The screenshot shows the 'Finish' page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is 'Finish'. The page displays the following configuration summary:

- Operation Mode: Bridge
- IP Address: 192.168.0.254
- Subnet Mask: 255.255.255.0
- SSID of Remote AP: 7200_5G
- Mode: 802.11a/n
- WDS: Disable
- Channel Width: 20/40MHz
- Security: WPA-PSK / WPA2-PSK
- Distance Setting: 0 km
- Wireless Radio: Enable
- SSID: TP-LINK_Outdoor_BD205C
- Security: WPA-PSK / WPA2-PSK

At the bottom of the page, there are two buttons: 'Back' and 'Finish'.

AP Router

If **AP Router** is selected, click **Next** and take the following steps:

1. The **WAN Connection Type** page will appear as shown below. Choose the suitable WAN connection type, and then click **Next**.

The screenshot shows a web interface with a navigation bar at the top containing the following tabs: QUICK SETUP, STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. The 'QUICK SETUP' tab is active. Below the navigation bar, the page title is 'WAN Connection Type'. The main content area contains the instruction: 'Select the connection type of WAN port according to your needs.:'. There are three radio button options:

- PPPoE - For this connection, you need to get the account name and password from your ISP.
- Dynamic IP - When connecting to the WAN, your router gets an IP address assigned by the DHCP server of your ISP.
- Static IP - With this type of connection, the device uses a permanent, static IP address assigned by your ISP.

 At the bottom of the page, there are two buttons: 'Back' and 'Next'.

2. The device supports three popular ways PPPoE, Dynamic IP and Static IP to connect to the Internet. If you are not sure of the connection type, please consult your ISP.
 - **PPPoE** - If your ISP delivers Internet through phone line and provides you with username and password, you should choose this type. Under this condition, you should fill in both *User Name* and *Password* that the ISP supplied, and then click **Next** to proceed. Please note that these fields are case-sensitive.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
WAN Settings					
User Name: <input type="text"/>					
Password: <input type="text"/> <input type="checkbox"/> Show					
Confirm Password: <input type="text"/> <input type="checkbox"/> Show					
<input type="button" value="Back"/> <input type="button" value="Next"/>					

- **Dynamic IP** - For this connection, Your ISP uses a DHCP server to assign your router an IP address for connecting to the Internet. You don't need to configure any parameters, Click **Next** to proceed.

- **Static IP** - This type of connection uses a permanent, fixed (static) IP address that your ISP assigned. In this type, you should fill in the IP address, Subnet Mask, Default Gateway, and DNS IP address manually, which are specified by your ISP. Then click **Next** to proceed.

The screenshot shows the WAN Settings configuration page. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is "WAN Settings". The main content area contains five input fields for network configuration, each with a label and a text box containing "0.0.0.0":

- IP Address: 0.0.0.0
- Subnet Mask: 0.0.0.0
- Default Gateway: 0.0.0.0
- Primary DNS: 0.0.0.0
- Secondary DNS: 0.0.0.0 (Optional)

At the bottom of the page, there are two buttons: "Back" and "Next".

3. After configuring WAN connection type, the **Wireless AP Settings** page will appear as shown below. Create an easy-to-remember name for your wireless network. We recommend to select **WPA-PSK/WPA2-PSK** in the **Security** box and enter the **PSK Password** below to prevent unauthorized access to your AP. Enter the distance between this device and the furthest client in **Distance Setting**. Then click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless AP Settings					
SSID: <input type="text" value="TP-LINK_Outdoor_BD205C"/>					
Mode: <input type="text" value="802.11a/n"/>					
Channel Width: <input type="text" value="20/40MHz"/>					
Channel/Frequency: <input type="text" value="Auto"/>					
Security: <input type="text" value="None"/>					
PSK Password: <input type="text"/> <input type="checkbox"/> Show					
We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.					
Distance Setting: <input type="text" value="0"/> (0-27.9)km					
MAXtreem: <input type="checkbox"/> Enable ?					
<input type="button" value="Back"/> <input type="button" value="Next"/>					

4. The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Finish					
Operation Mode: AP Router					
WAN Connection Type: Static IP					
IP Address: 192.168.2.10					
Subnet Mask: 255.255.255.0					
Default Gateway: 192.168.2.1					
Primary DNS: 192.168.0.3					
Secondary DNS: 192.168.1.3					
SSID: TP-LINK_Outdoor_BD205C					
Mode: 802.11a/n					
Channel Width: 20/40MHz					
Security: None					
Distance Setting: 0 km					
MAXtreem: Disable					
<input type="button" value="Back"/> <input type="button" value="Finish"/>					

AP Client Router (WISP Client)

If **AP Client Router (WISP Client)** is selected, click **Next** and take the following steps:

1. The **WAN Connection Type** page will appear as shown below. Choose the suitable WAN connection type, and then click **Next**.

The screenshot shows a web interface for configuring the WAN connection type. At the top, there is a navigation bar with tabs: QUICK SETUP (selected), STATUS, NETWORK, WIRELESS, MANAGEMENT, and SYSTEM. Below the navigation bar, the page title is "WAN Connection Type". The main content area contains the instruction "Select the connection type of WAN port according to your needs.:" followed by three radio button options:
- PPPoE - For this connection, you need to get the account name and password from your ISP.
- Dynamic IP - When connecting to the WAN, your router gets an IP address assigned by the DHCP server of your ISP.
- Static IP - With this type of connection, the device uses a permanent, static IP address assigned by your ISP.
At the bottom of the page, there are two buttons: "Back" and "Next".

2. The device supports three popular ways **PPPoE**, **Dynamic IP** and **Static IP** to connect to the Internet. To make sure the connection type your ISP provides, please refer to your ISP.

- **PPPoE** - If your ISP delivers Internet through phone line and provides you with username and password, you should choose this type. Under this condition, you should fill in both *User Name* and *Password* that the ISP supplied, and then click **Next** to proceed. Please note that these fields are case-sensitive.

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

WAN Settings

User Name:

Password: Show

Confirm Password: Show

Back Next

- **Dynamic IP** - For this connection, Your ISP uses a DHCP server to assign your router an IP address for connecting to the Internet. You don't need to configure any parameters, Click **Next** to proceed.
- **Static IP** - This type of connection uses a permanent, fixed (static) IP address that your ISP assigned. In this type, you should fill in the IP address, Subnet Mask, Default Gateway, and DNS IP address manually, which are specified by your ISP. Then click **Next** to proceed.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
WAN Settings					
IP Address: <input type="text" value="0.0.0.0"/>					
Subnet Mask: <input type="text" value="0.0.0.0"/>					
Default Gateway: <input type="text" value="0.0.0.0"/>					
Primary DNS: <input type="text" value="0.0.0.0"/>					
Secondary DNS: <input type="text" value="0.0.0.0"/> (Optional)					
<input type="button" value="Back"/> <input type="button" value="Next"/>					

3. After configuring WAN connection type, The **Wireless Client Settings** page will appear as shown below. Click **Survey** to search for wireless networks.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless Client Settings					
SSID of Remote AP: <input type="text"/> <input type="button" value="Survey"/>					
MAC of Remote AP: <input type="text"/> <input type="checkbox"/> Lock to AP					
Mode: <input type="text" value="802.11a/n"/>					
WDS: <input type="text" value="Auto"/>					
Channel Width: <input type="text" value="20/40MHz"/>					
Security: <input type="text" value="None"/>					
PSK Password: <input type="text" value="*****"/> <input type="checkbox"/> Show					
We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.					
Distance Setting: <input type="text" value="0"/> (0-27.9)km					
<input type="button" value="Back"/> <input type="button" value="Next"/>					

4. The AP list will appear as shown below. Select the desired wireless network and click **Connect**. It's possible that two or more networks use the same SSID in the AP list. **Lock to AP** can make the device connect to the specified AP you had connected before the next time.

QUICK SETUP
STATUS
NETWORK
WIRELESS
MANAGEMENT
SYSTEM

Wireless Client Settings

<input type="checkbox"/>	BSSID	SSID	MAXtream	Device Name	SNR (dB)	Signal / Noise (dBm)	Channel	Security
<input type="checkbox"/>	18-A6-F7-41-26-46	daisy 3	No		42	-53/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-27-7F-6E	SR20_5G	No		50	-45/-95	5220 (44)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-17-A6-E3	EAP-Show	No		14	-81/-95	5180 (36)	WPA2-PSK
<input type="checkbox"/>	D4-61-FE-5A-2A-00	das	No		11	-85/-96	5180 (36)	WPA-PSK/WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-54-DB	deco	No		35	-61/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-1F	deco	No		30	-66/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	50-C7-BF-48-57-74	deco	No		47	-49/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-54-DB		No		37	-59/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-1F		No		31	-65/-96	5200 (40)	WPA2-PSK
<input type="checkbox"/>	56-C7-BF-48-57-74		No		47	-49/-96	5200 (40)	WPA2-PSK

WPA-PSK/WPA2

Back Refresh Connect Lock to AP

5. If the root AP needs password to be connected, you should select the same **Mode**, **Channel Width** and **Security** type and enter the same *PSK Password* as entered on the root AP/router. Enter the distance between this device and the root AP/router in *Distance setting*. Then click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless Client Settings					
SSID of Remote AP:		<input type="text" value="7200_5G"/>		<input type="button" value="Survey"/>	
MAC of Remote AP:		<input type="text" value="50-C7-BF-01-88-1F"/>		<input type="checkbox"/> Lock to AP	
Mode:		802.11a/n		▼	
WDS:		Auto		▼	
Channel Width:		20/40MHz		▼	
Security:		WPA-PSK / WPA2-PSK		▼	
PSK Password:		<input type="password" value="*****"/>		<input type="checkbox"/> Show	
We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.					
Distance Setting:		<input type="text" value="0"/>		(0-27.9)km	
		<input type="button" value="Back"/>		<input type="button" value="Next"/>	

6. Create a new **SSID** and **PSK Password** for the local wireless network. The wireless AP settings for the local network will be set the same as your root AP by default. Click **Next**.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Wireless AP Settings					
Wireless Radio:		<input checked="" type="checkbox"/> Enable			
SSID:		<input type="text" value="TP-LINK_Outdoor_BD205C"/>			
Security:		WPA-PSK / WPA2-PSK ▼			
PSK Password:		<input type="password" value="*****"/>		<input type="checkbox"/> Show	
We do not recommend using WEP encryption. You can go to WIRELESS page to configure the encryption mode.					
		<input type="button" value="Back"/>		<input type="button" value="Next"/>	

- The **Finish** page will appear and display what you've configured previously. If you want to modify any parameter, click **Back** to reconfigure it. If all are confirmed, click **Finish** to complete the configuration.

QUICK SETUP	STATUS	NETWORK	WIRELESS	MANAGEMENT	SYSTEM
Finish					
Operation Mode: AP Client Router (WISP Client)					
WAN Connection Type: Static IP					
IP Address: 192.168.2.10					
Subnet Mask: 255.255.255.0					
Default Gateway: 192.168.2.1					
Primary DNS: 192.168.0.1					
Secondary DNS: 192.168.1.2					
SSID of Remote AP: 7200_5G					
Mode: 802.11a/n					
WDS: Disable					
Channel Width: 20/40MHz					
Security: WPA-PSK / WPA2-PSK					
Distance Setting: 0 km					
Wireless Radio: Enable					
SSID: TP-LINK_Outdoor_BD205C					
Security: WPA-PSK / WPA2-PSK					
<input type="button" value="Back"/> <input type="button" value="Finish"/>					

Chapter 4 Status Tab

The **Status** tab displays a summary of the link status information, current values of the basic configuration settings (depending on the operating mode), network settings and information, and traffic statistics.

QUICK SETUP
STATUS
NETWORK
WIRELESS
MANAGEMENT
SYSTEM

Device Information

Device Name: CPE510
 Device Model: CPE510 v1.1
 Firmware Version: 2.1.0 Build 20170609 Rel. 57434 (0000)
 System Time: 2015-01-01 00:05:11
 Uptime: 0 days 00:05:12
 CPU: 2%
 Memory: 57%

Wireless Settings

MAXtream: OFF
 Channel/Frequency: 149 / 5745MHz
 Channel Width: 20/40MHz
 IEEE802.11 Mode: A/N Mixed
 Max TX Rate: 300.0Mbps
 Transmit Power: 23dBm
 Distance: 0.0km

Wireless Signal Quality

Signal Strength: N/A
 Noise Strength: N/A
 SNR: N/A
 Transmit CQ: 100

Radio Status

AP: Enable
 MAC Address: 30-B5-C2-BD-20-5C
 SSID: TP-LINK_Outdoor_BD205C
 Security Mode: None
 Connected Stations: 0

LAN

MAC Address: 30-B5-C2-BD-20-5C
 IP Address: 192.168.0.254
 Subnet Mask: 255.255.255.0
 Port0: Unplugged
 Port1: 100Mbps - FD

Client: Disabled
 MAC Address: N/A
 Security Mode: N/A
 WDS: N/A
 Root AP BSSID: N/A
 Root AP SSID: N/A
 TX Rate: N/A
 RX Rate: N/A
 Connection Time: N/A

WAN

Connection Type: N/A
 MAC Address: N/A
 IP Address: N/A
 Subnet Mask: N/A
 Default Gateway: N/A
 DNS Server: N/A

Monitor

Throughput
Stations
Interfaces
ARP Table
Routes
DHCP Clients

LAN0

— RX
 — TX

WLAN0

— RX
 — TX


Kbps

Kbps

Status Information


- **Device Information**

Device information displays the customizable name, model, firmware version, system time, uptime, CPU and memory of the device.



- **Wireless Settings**

Wireless settings display the relative wireless parameters of the current device. You can change the parameters in [Wireless tab](#).



MAXstream Displays whether the MAXstream function is ON.

Channel/Frequency Displays the channel number and corresponding operating frequency. The device uses the channel and radio frequency specified to transmit and receive data. Valid channel and frequency ranges will vary depending on local regulations.

Channel Width Displays the spectral width of the radio channel used by the device.

IEEE802.11 Mode Displays the radio standard used for operation of your device.


Max TX Rate Displays the data rate at which the device should transmit wireless packets.

Transmit Power Displays the current transmit power of the device.

Distance Displays the wireless coverage distance where the client devices can be placed from the AP to get good wireless performance. You can change the value in [Wireless Advanced Settings](#).

- **Wireless Signal Quality**

Status of wireless signal quality displays the parameters of the received wireless signal in the modes of Client, Repeater (Range Extender), Bridge and AP Client Router. The parameters here is not applicable for other two modes.



Signal Strength	Displays the received wireless signal strength of the root AP.
Noise Strength	Displays the received environmental noise from wireless interference on the operating frequency.
SNR	Signal to Noise Ratio, the power ratio between the received wireless signal strength and the environmental noise strength. Generally, in order to achieve the best performance, users need to adjust the antenna to get the best SNR.
Transmit CCQ	Displays the wireless Client Connection Quality (CCQ). CCQ refers to the ratio of current effective transmission bandwidth and the theoretically maximum available bandwidth. CCQ reflects the actual link condition.

- **Radio Status**

Radio status shows the MAC address, SSID, security mode and connected station number of the enabled AP. If the Client mode is enabled, the information of MAC address, security mode, WDS, root AP BSSID, root AP SSID, TX rate, RX rate and connection time of the client will also be displayed.

Radio Status
AP: Enabled
MAC Address: 98-DE-D0-88-6C-84
SSID: TP-LINK_Outdoor_886C84
Security Mode: None
Connected Stations: 0
Client: Disabled
MAC Address: N/A
Security Mode: N/A
WDS: N/A
Root AP BSSID: N/A
Root AP SSID: N/A
TX Rate: N/A
RX Rate: N/A
Connection Time: N/A

AP	Displays whether the AP function is Enabled or Disabled. It is enabled in Access Point, Repeater, Bridge, AP Router and AP Client Router modes and disabled in Client mode by default.
MAC Address	Displays the MAC address of AP interface or client interface.
SSID	Displays the wireless network name (SSID).
Security Mode	Displays the security mode you've chosen for your wireless network. There are three security modes: WPA-PSK, WPA and WEP. None means that no security mode is selected and all the hosts are allowed to access the wireless network.
Connected Station	Displays the number of the connected stations.
Client	Displays whether the Client function is Enabled or Disabled. It is enabled in Client, Repeater, Bridge and AP Client Router modes and disabled in Access Point and AP Router modes by default.
WDS	Displays whether the Wireless Distribution System (WDS) is enabled or not.
Root AP BSSID	Displays the basic service set identification (MAC address) of root AP.
Root AP SSID	Displays the wireless network name of root AP.
TX Rate	Displays the data rate at which the device transmits wireless packets.
RX Rate	Displays the data rate at which the device receives wireless packets.

Connection Time Displays the amount of time the device has been connected to the root AP.

- **LAN**

It displays the relative LAN parameters of the current device. You can change the parameters in **Network Tab**.

LAN
MAC Address: 98-DE-D0-88-6C-84
IP Address: 192.168.0.254
Subnet Mask: 255.255.255.0
Port0: Unplugged
Port1: 100Mbps - FD

MAC Address Displays the MAC address of the device.

IP Address Displays the IP address of the device.

Subnet Mask Displays the Subnet Mask of the LAN.

Port Displays the current status of the LAN Ethernet port connections and the Maximum transmission rate of the plugged port.

- **WAN**

It displays the relative WAN parameters of the current device. You can change the parameters in **Network Tab**.

WAN
Connection Type: N/A
MAC Address: N/A
IP Address: N/A
Subnet Mask: N/A
Default Gateway: N/A
DNS Server: N/A

Connection Type Displays the WAN connection type of the device.

MAC Address Displays the MAC address of the device's WAN port.

IP Address Displays the IP address of the device's WAN port.

Subnet Mask Displays the Subnet Mask of the WAN.

Default Gateway Displays the default gateway.

DNS Server


Displays the current DNS IP address.

Monitor

The monitor displays the data changes of throughput, Stations, Interfaces, ARP table, Routes, DHCP Clients and Dynamic WAN of the device.

- Throughput**

Throughput displays the current data traffic on the interfaces of LAN, WLAN and BRIDGE in both graphical and numerical form. You can choose the specific interface to monitor from the drop-down list above the chart.



- Stations**

In the modes with the AP function enabled, you can monitor the information of all the stations that are connected to the device.

Throughput Stations Interfaces ARP Table Routes DHCP Clients Dynamic WAN									
MAC Address	Device Name	Associated SSID	Signal / Noise(dBm)	CCQ (%)	Negotiated Rate(Mbps)	Data TX / RX (Kbps)	Distance (km)	IP Address	Connection Time
00-0A-EB-21-01-10	Jim	TP-LINK_Out...	-50/-105	93	300.0	169/3962	0.00	192.168.0.102	0 days 00:04:30

Auto Refresh

MAC Address

Displays the MAC address of the station.

Device Name

Displays the station's host name.

Associated SSID

The SSID that the station connected to.

Signal/Noise (dBm)

Signal to Noise Ratio, the power ratio between the received wireless signal strength and the environmental noise strength. Generally, in order to achieve the best performance, users need to adjust the antenna to get the best SNR.

CCQ (%)	Displays the wireless Client Connection Quality (CCQ) of the station.
Negotiate Rate (Mbps)	Displays the station's data rates of the last transmitted packets.
Data TX/RX (kbps)	Displays the station's average data rates of the transmitted and received packet over the connection time.
Distance (km)	Displays the distance between the station and the device.
IP Address	Displays the IP address of the station.
Connection Time	Displays the connection duration.
Auto Refresh	If Auto Refresh is checked, parameters in the table will refresh automatically.

- Interfaces**

The table displays the relevant information of each interface including MAC, IP address, etc.

Throughput Stations Interfaces ARP Table Routes DHCP Clients							
Interface	MAC	IP Address	MTU	RX packets	RX Bytes	TX packets	TX Bytes
LAN0	98-DE-D0-88-6C-84	0.0.0.0	1500	0	0	0	0
LAN1	98-DE-D0-88-6C-84	0.0.0.0	1500	20945	1M	21169	20M
BRIDGE	98-DE-D0-88-6C-84	192.168.0.254	1500	11819	1M	21170	20M
WLAN0	98-DE-D0-88-6C-84	0.0.0.0	1500	0	0	5321	1M

Auto Refresh

MAC	Displays the MAC address of the interface.
IP Address	Displays the IP address of the interface.
MTU	Displays the Maximum Transmission Unit (MTU), which is the maximum packet size (in bytes) that a network interface can transmit.
RX packets	Displays the total amount of packets received by the interface after the device is powered on.
RX Bytes	Displays the total amount of data (in bytes) received by the interface after the device is powered on.
TX packets	Displays the total amount of packets transmitted by the interface after the device is powered on.
TX Byte	Displays the total amount of data (in bytes) transmitted by the interface after the device is powered on.

Auto Refresh If **Auto Refresh** is checked, parameters in the table will refresh automatically.

- **ARP table**

Lists all the entries of the Address Resolution Protocol (ARP) table currently recorded on the device. ARP is used to associate each IP address to the unique hardware MAC address of each device on the network.

Throughput Stations Interfaces <u>ARP Table</u> Routes DHCP Clients		
IP Address	MAC	Interface
192.168.0.200	00-19-66-35-E1-B0	BRIDGE
192.168.0.16	00-0A-EB-13-23-7B	BRIDGE
192.168.0.61	F4-F2-6D-C3-28-62	BRIDGE
169.254.60.119	DC-9B-9C-D3-17-61	BRIDGE

Auto Refresh

IP Address Displays the IP address assigned to a network device.

MAC Displays the MAC address of the device.

Interface Displays the interface that connects to the device.

Auto Refresh If **Auto Refresh** is checked, parameters in the table will refresh automatically.

- **Routes**

List all the entries in the system routing table. PharOS examines the destination IP address of each data packet traveling through the system and chooses the appropriate interface to forward the packet to. Routing depends on static routing rules, which are registered in the system routing table. Static routes to specific hosts, networks, or the default gateway are set up automatically according to the IP configuration of all the Interfaces.

Throughput Stations Interfaces ARP Table <u>Routes</u> DHCP Clients			
Destination	Gateway	SubnetMask	Interface
192.168.0.0	0.0.0.0	255.255.255.0	BRIDGE

Auto Refresh

Destination Displays the IP address of the destination device or destination network.

Gateway Displays the IP address of the appropriate gateway.

Subnet Mask Displays the Subnet Mask of the destination device.

Interface Displays the interface that the destination device is on.

Auto Refresh

If **Auto Refresh** is checked, parameters in the table will refresh automatically.

- **DHCP Clients**

DHCP Clients display the current information of the clients including client names, MAC addresses, IP addresses assigned by the device's DHCP server and their lease time.

Client Name	MAC Address	Assigned IP	Lease Time
Jim	00-0A-EB-21-01-10	192.168.0.102	0 days 01:57:57

Auto Refresh

- **Client Name**

Displays the device name of the client.

- **MAC Address**

Displays the client's MAC Address.

- **IP Address**

Displays the IP address assigned to the client.

- **Lease Time**

Displays the time of the DHCP client leased. Before the time is up, DHCP client will request to renew the lease automatically.

- **Auto Refresh**

If **Auto Refresh** is checked, parameters in the table will refresh automatically.

- **Dynamic WAN**

NOTE:

This submenu is only available in **AP router** mode and **AP client router (WISP Client)** mode when the WAN connection type is PPPoE, PPTP, L2TP or Dynamic.

Dynamic WAN displays the WAN connection status of your device.

Throughput	Stations	Interfaces	ARP Table	Routes	DHCP Clients	Dynamic WAN								
<p>DHCP Status</p> <table border="0"> <tr> <td>Status: Disconnected</td> <td>Primary DNS: 0.0.0.0</td> </tr> <tr> <td>IP Address: 0.0.0.0</td> <td>Secondary DNS: 0.0.0.0</td> </tr> <tr> <td>Subnet Mask: 0.0.0.0</td> <td>Connection Uptime: 0 days 00:00:00</td> </tr> <tr> <td>Gateway IP: 0.0.0.0</td> <td><input type="button" value="Obtain"/> <input type="button" value="Release"/></td> </tr> </table> <p style="text-align: right;"><input checked="" type="checkbox"/> Auto Refresh</p>							Status: Disconnected	Primary DNS: 0.0.0.0	IP Address: 0.0.0.0	Secondary DNS: 0.0.0.0	Subnet Mask: 0.0.0.0	Connection Uptime: 0 days 00:00:00	Gateway IP: 0.0.0.0	<input type="button" value="Obtain"/> <input type="button" value="Release"/>
Status: Disconnected	Primary DNS: 0.0.0.0													
IP Address: 0.0.0.0	Secondary DNS: 0.0.0.0													
Subnet Mask: 0.0.0.0	Connection Uptime: 0 days 00:00:00													
Gateway IP: 0.0.0.0	<input type="button" value="Obtain"/> <input type="button" value="Release"/>													

Status

Displays the WAN status is disconnected or connected.

IP Address	Displays the IP address of the WAN.
Subnet Mask	Displays the Subnet Mask of the WAN.
Gateway IP	Displays the address of the gateway.
Primary DNS/Secondary DNS	Displays the DNS IP address provided by your ISP.
Connection Uptime	Displays the time that the latest WAN connection lasts.
Auto Refresh	If Auto Refresh is checked, parameters in the table will refresh automatically.

Click **Obtain** to gain the WAN IP address from DHCP server, and click **Release** to release the WAN IP address.

Chapter 5 Network Tab

On **Network** Tab, you can configure the parameters of WAN, LAN, Management VLAN, Forwarding, Security, Access Control, Static Routing, Bandwidth control and IP&MAC Binding.

tp-link PHAROS About Support Log Out

Operation Mode: AP Client Router Tools

QUICK SETUP STATUS NETWORK WIRELESS MANAGEMENT SYSTEM

WAN

Connection Type: Dynamic

Advanced Settings

MTU Size: 1500

Use These DNS Servers: Enable

WAN MAC Address: 30-B5-C2-BD-20-5D

Your PC's MAC Address: FC-AA-14-55-EB-0E

LAN

Connection Type: Static

IP Address: 192.168.0.254

Netmask: 255.255.255.0

Gateway IP: 0.0.0.0

Primary DNS: 0.0.0.0

Secondary DNS: 0.0.0.0

IGMP Proxy: Enable

DHCP Server: Enable

DHCP Server

Start IP Address: 192.168.0.100 End IP Address: 192.168.0.199

Default Gateway: 192.168.0.254 Default Domain:

Primary DNS: 0.0.0.0 Secondary DNS: 0.0.0.0

Lease Time: 120 minutes

Address Reservation

<input type="checkbox"/>	Enable	MAC	IP
--	--	--	--

Management VLAN Interface

Management Interface: Enable

Forwarding

Security

Access Control

Static Routing

Bandwidth Control

IP & MAC Binding

If you've made any change of the parameters, click **Apply** to make the configuration take effect. There will be a blue bar at the top of the page to remind you to save the configuration. Click **Save Changes** when you finish all settings, otherwise all the settings will be recovered to last saved settings at reboot or power off.

You have unsaved changes. Would you like to save your changes?

Save

WAN

NOTE:

WAN submenu is only available on **AP router** mode and **AP client router (WISP Client)** mode.

The screenshot shows the WAN configuration page with the 'Connection Type' dropdown menu open. The menu options are Static, Dynamic (selected), PPPoE, L2TP, and PPTP. Below the dropdown, there are fields for 'MTU Size', 'WAN MAC Address', and 'Your PC's MAC Address'. There are also buttons for 'Restore to Factory MAC' and 'Clone PC's MAC'. An 'Apply' button is at the bottom right.

There are five WAN connection types: Static, Dynamic, PPPoE, L2TP, and PPTP. Select the suitable one to configure the IP parameters of the WAN on the screen below. If you are not sure of the connection type, please consult your ISP.

- **Static**

This connection type uses a permanent, fixed (static) IP address that your ISP assigned. In this type, you should fill in the IP address, Netmask, Gateway IP, and DNS IP address manually, which are specified by your ISP.

The screenshot shows the WAN configuration page with 'Connection Type' set to 'Static'. Fields for 'IP Address', 'Netmask', 'Gateway IP', 'Primary DNS', and 'Secondary DNS' are visible. The 'Advanced Settings' section is expanded, showing 'MTU Size', 'WAN MAC Address', and 'Your PC's MAC Address'. There are also buttons for 'Restore to Factory MAC' and 'Clone PC's MAC'. An 'Apply' button is at the bottom right.

IP Address	Enter the IP address provided by your ISP.
Netmask	Enter the Netmask provided by your ISP. Normally use 255.255.255.0.
Gateway IP	Enter the gateway IP address provided by your ISP.
Primary DNS	Enter the DNS IP address provided by your ISP.
Secondary DNS	Enter alternative DNS IP address if your ISP provides.
MTU Size	The normal MTU (Maximum Transmission Unit) value for most Ethernet networks is 1500 Bytes. For some ISPs you need to modify the MTU. But this is rarely required, and should not be done unless you are sure it is necessary for your ISP connection.
WAN MAC Address	This field displays the current MAC address of the WAN port. If your ISP requires that you register the MAC address, enter the correct MAC address into this field. The format for the MAC Address is XX-XX-XX-XX-XX-XX (X is any hexadecimal digit). Click Restore Factory MAC to restore the MAC address of WAN port to the factory default value.
Your PC's MAC Address	This field displays the MAC address of the PC that is managing the router. Some ISPs require that you should register the MAC address of your PC. If the MAC address is required, you can click Clone PC's MAC to set the WAN MAC address the same as your management PC's MAC.

- **Dynamic**

For this connection, Your ISP uses a DHCP server to assign your router an IP address for connecting to the Internet. You don't need to configure any parameters.

The screenshot shows the WAN configuration window with the following settings:

- Connection Type:** Dynamic
- Advanced Settings:**
 - MTU Size:** 1500
 - Use These DNS Servers:** Enable
 - Primary DNS:** 0.0.0.0
 - Secondary DNS:** 0.0.0.0
 - WAN MAC Address:** 30-B5-C2-BD-20-5D (with a **Restore to Factory MAC** button)
 - Your PC's MAC Address:** FC-AA-14-55-EB-0E (with a **Clone PC's MAC** button)
- Apply** button

MTU Size The normal MTU (Maximum Transmission Unit) value for most Ethernet networks is 1500 Bytes. For some ISPs you need to modify the MTU. But this is rarely required, and should not be done unless you are sure it is

necessary for your ISP connection.

Use These DNS Servers If your ISP gives you one or two DNS IP addresses, select Use These DNS Servers and enter the Primary DNS and Secondary DNS into the correct fields. Otherwise, the DNS servers will be assigned from ISP dynamically.

Primary DNS Enter the DNS IP address provided by your ISP.

Secondary DNS Enter another DNS IP address provided by your ISP.

WAN MAC Address This field displays the current MAC address of the WAN port. If your ISP binds the MAC address of your previous computer/router, enter the correct MAC address into this field. The format for the MAC Address is XX-XX-XX-XX-XX-XX (X is any hexadecimal digit). Click Restore Factory MAC to restore the MAC address of WAN port to the factory default value.

Your PC's MAC Address This field displays the MAC address of the PC that is managing the router. Some ISPs require that you should register the MAC address of your PC. If the MAC address is required, you can click **Clone PC's MAC** to set the WAN MAC address the same as your management PC's MAC.

- **PPPoE**

If your ISP delivers Internet through phone line and provides you with username and password, you should choose this type. Under this condition, you should fill in both User Name and Password that the ISP supplied, note that these fields are case-sensitive.

The screenshot shows the WAN configuration interface. At the top, the title is "WAN". Below it, the "Connection Type" is set to "PPPoE". There are "Connect" and "Disconnect" buttons. The "User Name" and "Password" fields are empty, with a "Show" checkbox next to the password field. Below these, there are checkboxes for "Use These DNS Servers" (disabled) and "Connection Mode" set to "Automatic". The "Second Connection" is set to "disabled".

An "Advanced Settings" section is expanded, showing:

- MTU Size: 1480
- Service Name: (empty)
- AC Name: (empty)
- Detect Interval: 0 seconds
- Use ISP-Specified IP: (disabled)
- Use These DNS Servers: (disabled)
- WAN MAC Address: 30-B5-C2-BD-20-5D, with a "Restore to Factory MAC" button.
- Your PC's MAC Address: FC-AA-14-55-EB-0E, with a "Clone PC's MAC" button.

An "Apply" button is located at the bottom right of the form.

User Name/Password Enter the User Name and Password provided by your ISP. These fields are case-sensitive.

User These DNS Servers

Connection Mode Please choose the Connection mode.

- **On Demand** - You can configure the device to disconnect your Internet connection after a specified period of inactivity (**Idle Time**). If your Internet connection has been terminated due to inactivity, Connection **on Demand** enables the device to automatically re-establish your connection when you attempt to access the Internet again. The default Idle Time is 15 minutes. If your Internet connection is expected to remain active all the time, enter **0** in the **Idle Time** field. Users those pay by time for their Internet access can choose this mode to save their Internet-access fee.

Connection Mode: On Demand
Idle Time: 15 minutes

NOTE: Sometimes the connection cannot be disconnected although you specify a time to **Idle Time** (0~99 minutes) because some applications visit the Internet continually in the background.

- **Automatic** - Connect automatically after the device is disconnected. Users those are charged a flat monthly fee can choose this mode.
- **Time-based** - You can configure the device to make it connect or disconnect based on time. Enter the start time in **From (HH:MM)** for connecting and end time in **To (HH:MM)** for disconnecting. Users those need to control the time period of Internet access can choose this mode.

Connection Mode: Time-based
From(HH:MM): 00:00
To(HH:MM): 23:59

- **Manual** - You can configure the device to make it connect or disconnect manually. After a specified period of inactivity (**Idle Time**), the device will disconnect your Internet connection, and you must click **Connect** manually to access the Internet again. If your Internet connection is expected to remain active all the times, enter **0** in the **Idle Time** field. Otherwise, enter the desired Idle Time in minutes you wish to use. Users those pay by time for their Internet access can choose this mode to save their Internet-access fee.

Connection Mode: Manual
Idle Time: 15 minutes

Secondary Connection	<p>If your ISP provides an extra Connection type such as Dynamic/Static IP to connect to a local area network, you can activate this secondary connection.</p> <ul style="list-style-type: none"> • Disable - The Secondary Connection is disabled by default, so there is PPPoE connection only. This is recommended. • Dynamic IP - Use dynamic IP address to connect to the local area network provided by ISP. • Static IP - Use static IP address to connect to the local area network provided by ISP.
MTU Size	<p>The default MTU (Maximum Transmission Unit) size is 1480 bytes, which is usually appropriate. For some ISPs, you need modify the MTU. This should not be done unless your ISP told you to.</p>
Service Name/AC Name	<p>Do not change it unless your ISP told you to.</p>
Detect Interval	<p>The default value is 0. You can input the value between 0 and 120. The device will detect Access Concentrator online every interval seconds. If the value is 0, it means not detecting.</p>
Use ISP-Specified IP	<p>If your service provider give you an IP address along with the user name and password, Enable "Use ISP-specified IP" and enter the IP address, which is provided by your ISP.</p>
Use These DNS Servers	<p>If the ISP specifies a DNS server IP address for you, Enable Use These DNS Server, and fill the Primary DNS and Secondary DNS fields below. Otherwise, the DNS servers will obtain automatically from ISP.</p>
WAN MAC Address	<p>This field displays the current MAC address of the WAN port. If your ISP binds the MAC address of your previous computer/router, enter the correct MAC address into this field. The format for the MAC Address is XX-XX-XX-XX-XX-XX (X is any hexadecimal digit). Click Restore Factory MAC to restore the MAC address of WAN port to the factory default value.</p>
Your PC's MAC Address	<p>This field displays the MAC address of the PC that is managing the router. You can click Clone PC's MAC to set the WAN MAC address the same as your management PC's MAC.</p>

Click **Connect** to connect immediately. Click **Disconnect** to disconnect immediately. You can check and control the status of WAN connection on **Monitor > Dynamic WAN** page.

- **L2TP/PPTP**

The configuration steps of these two WAN connections are the same. Take L2TP as an example to introduce.

Server IP/Name Enter the server IP address or the domain name given by your ISP.

User Name/Password Enter the *User Name* and *Password* provided by your ISP. These fields are case-sensitive.

Connection Mode

- **On Demand** - You can configure the device to disconnect your Internet connection after a specified period of inactivity (**Idle Time**). If your Internet connection has been terminated due to inactivity, **Connect on Demand** enables the device to automatically re-establish your connection when you attempt to access the Internet again. The default Idle Time is 15 minutes. If your Internet connection is expected to remain active all the time, enter **0** in the **Idle Time** field. Users those pay by time for their Internet access can choose this mode to save their Internet-access fee.

NOTE: Sometimes the connection cannot be disconnected although you specify a time to **Idle Time** (0~99 minutes) because some applications visit the Internet continually in the background.

- **Automatic** - Connect automatically after the device is disconnected. Users those are charged a flat monthly fee can choose this mode.
- **Manual** - You can configure the device to make it connect or disconnect manually. After a specified period of inactivity (**Idle Time**), the device will disconnect your Internet connection, and you must click **Connect** manually to access the Internet again. If you want your Internet connection to remain active all the times, enter **0** in the **Idle Time** field. Otherwise, enter the desired Idle Time in minutes you wish to use. Users those pay by time for their Internet access can choose this mode to save their Internet-access fee.

Secondary Connection

If your ISP provides a Connection type such as Dynamic/Static IP to connect to a local area network, you can activate this secondary connection.

- **Dynamic** - Use dynamic IP address to connect to the local area network provided by ISP.
- **Static** - Use static IP address to connect to the local area network provided by ISP.

MTU Size

The default MTU (Maximum Transmission Unit) size is 1460 bytes in L2TP and 1420 bytes in PPTP, which is usually fine. For some ISPs, you need modify the MTU. This should not be done unless you are sure it is necessary for your ISP.

WAN MAC Address

This field displays the current MAC address of the WAN port, which is used for the WAN port. If your ISP requires that you register the MAC address, enter the correct MAC address into this field. The format for the MAC Address is XX-XX-XX-XX-XX-XX (X is any hexadecimal digit). Click **Restore Factory MAC** to restore the MAC address of WAN port to the factory default value.

Your PC's MAC Address

This field displays the MAC address of the PC that is managing the router. If the MAC address is required, you can click **Clone PC's MAC** to set the WAN MAC address the same as your management PC's MAC.

Click **Connect** to connect immediately. Click **Disconnect** to disconnect immediately. You can check and control the status of WAN connection on **Monitor > Dynamic WAN** page.

LAN

The display of this submenu is different in modes. The page of **AP router** mode and **AP client router (WISP Client)** mode is shown as below. In these two modes, static is the only one connection type.

LAN

Connection Type:

IP Address:

Netmask:

Gateway IP:

Primary DNS:

Secondary DNS:

IGMP Proxy: Enable

DHCP Server: Enable

DHCP Server

Start IP Address: End IP Address:

Default Gateway: Default Domain:

Primary DNS: Secondary DNS:

Lease Time: minutes

Address Reservation

<input type="checkbox"/>	Enable	MAC	IP
--	--	--	--

While the page of **Access Point** mode, **Client** mode, **Repeater (Range extender)** mode and **Bridge** mode is shown as below. There are two connection types including dynamic and static.

LAN

Connection Type:

Fallback IP: Enable

DHCP Fallback IP:

DHCP Fallback Mask:

Primary DNS:

Secondary DNS:

IGMP Proxy: Enable

LAN
⌵

Connection Type: Static

IP Address: 192.168.0.254

Netmask: 255.255.255.0

Gateway IP: 0.0.0.0

Primary DNS: 0.0.0.0

Secondary DNS: 0.0.0.0

IGMP Proxy: Enable

DHCP Server: Enable

⌵ DHCP Server

Start IP Address: 192.168.0.100

Default Gateway: 192.168.0.254

Primary DNS: 0.0.0.0

Lease Time: 120 minutes

End IP Address: 192.168.0.199

Default Domain:

Secondary DNS: 0.0.0.0

Address Reservation

+ Add
⚙ Edit
⊖ Delete

	Enable	MAC	IP
--	--	--	--

Apply

Connection type There is only one LAN Connection type **Static** in AP Router mode and AP Client Router (WISP Client) mode. While there are **Static** and **Dynamic** of Connection types in Access Point mode, Client mode, Repeater (Range Extender) mode and Bridge mode.

IP Address Enter the IP address of your AP/router (factory default: 192.168.0.254).

Netmask Enter the Netmask provided by your ISP. Normally use 255.255.255.0 as the netmask.

Gateway IP Enter the IP address of the gateway for your device.

Primary DNS Enter the primary DNS IP address provided by your ISP. Please consult your ISP if you don't know the DNS value. The factory default setting is 0.0.0.0.

Secondary DNS Enter the secondary DNS IP address of alternative DNS server if your ISP two DNS servers. The factory default setting is 0.0.0.0.

IGMP Proxy IGMP (Internet Group Management Protocol) works for IPTV multicast stream. If you want to watch IPTV, **Enable** it.

DHCP Server If the built-in DHCP server is expected to assign IP addresses to clients connected to the wireless interface and LAN interface, **Enable** it.

Fallback IP	When Dynamic IP is selected as the connection type, you can enable this function. The fallback IP will be used as the LAN IP when a DHCP server is not found.
DHCP Fallback IP	Specify the IP address for the device to use if a DHCP server is not found.
DHCP Fallback Mask	Specify the mask for the device to use if a DHCP server is not found.
Start IP Address	This field specifies the first address in the IP Address pool. 192.168.0.100 is the default start IP address.
End IP Address	This field specifies the last address in the IP Address pool. 192.168.0.199 is the default end IP address.
Default Gateway	Enter the IP address of the gateway for your LAN. The factory default setting is 192.168.0.254.
Default Domain	Enter the domain name of your DHCP server. You can leave the field blank.
Primary DNS	Enter the DNS IP address for the LAN. The factory default setting is 0.0.0.0.
Secondary DNS	Enter the IP address of alternative DNS server if there are two DNS servers. The factory default setting is 0.0.0.0.
Lease Time	Enter the amount time of the leased IP address assigned by the DHCP server. Before the time is up, DHCP client will request to renew the lease automatically and DHCP server would not assign this IP address to other clients.

Address Reservation

Address Reservation will enable you to specify a reserved IP address for a PC on the local area network, so the PC will always obtain the same IP address each time when it starts up. Reserved IP addresses could be assigned to servers that require permanent IP settings.

Enable	MAC	IP
<input checked="" type="checkbox"/>	6c-62-6d-f7-2e-82	192.168.0.102
--	--	--

Save Cancel

To Reserve IP addresses:

Click **Add** in the table of Address Reservation.

Enter the **MAC address** in the format of XX-XX-XX-XX-XX-XX and the **IP address** in dotted-decimal notation of the station you want to add.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

Management VLAN

Management VLAN provides a safer way for you to manage the device. With Management VLAN enabled, only the hosts in the management VLAN can manage the device. Since most hosts cannot process VLAN TAGs, connect the management host to the network via a switch, and set up correct VLAN settings for the switches on the network to ensure the communication between the host and the device in the management VLAN.

Management VLAN Interface

Management Interface: Enable ?

VLAN ID:

Apply

Management VLAN

Enable Management VLAN. By default, it is disabled.

VLAN ID

Specify the Management VLAN ID. The valid values are from 2 to 4094.

Forwarding

The Forwarding feature is available only in AP Router mode and AP Client Router (WISP Client) mode.

The IP address used on the Internet is public IP address, while IP address used on local area network is private IP address. The hosts using private IP addresses cannot access the Internet directly and vice versa.

The hosts using private IP addresses visit Internet through NAT (Network Address Translation) technology. NAT can transfer private IP addresses into public IP addresses to realize the communication from internal hosts to external hosts.

If the hosts on the Internet want to visit the hosts on local area network, the forwarding function should be used, including DMZ, Virtual server, Port triggering and UPnP.

Forwarding ⌵

DMZ: Enable ?

DMZ IP:

ALG: FTP ALG TFTP ALG H323 ALG RTSP ALG ?

Virtual Server: Enable ?

+ Add ⚙ Edit - Delete

	Enable	IP	Internal Port	Service Port	Protocol
--	--	--	--	--	--

Port Trigger: Enable

+ Add ⚙ Edit - Delete

	Enable	Incoming Port	Trigger Port	Protocol
--	--	--	--	--

UPnP: Enable ?

↻ Refresh

	App Description	External Port	Internal Port	Protocol	IP Address	Status
--	--	--	--	--	--	--

Apply

DMZ

Check the **Enable** box to use the DMZ function. DMZ (Demilitarized Zone) specifically allows one computer/device behind NAT to become "demilitarized", so all packets from the external network are forwarded to this computer/device. The demilitarized host is exposed to the wide area network, which can realize the unlimited bidirectional communication between internal hosts and external hosts.

DMZ IP

Specify the IP address of the local host network device. The DMZ host device will be completely exposed to the external network. Any PC that was used for a DMZ must have a static or reserved IP Address because its IP Address may change when using the DHCP function.

ALG

Common NAT only translates the address of packets at network layer and the port number at transport layer but cannot deal with the packets with embedded source/destination information in the application layer. Application layer gateway (ALG) can deal with protocols with embedded source/destination information in the application payload. Some protocols such as FTP, TFTP, H323 and RTSP require ALG (Application Layer Gateway) support to pass through NAT.

- **FTP ALG** - Allows FTP clients and servers to transfer data across NAT.
- **TFTP ALG** - Allows TFTP clients and servers to transfer data across NAT.
- **H323 ALG** - Allows Microsoft NetMeeting clients to communicate across NAT.
- **RTSP ALG** - Allows some media player clients to communicate with some streaming media servers across NAT.

Virtual Server

Check the **Enable** box to use the virtual server function. Virtual servers can be used for setting up public services on your local area network, such as DNS, Email and FTP. A virtual server is defined as a service port, and all requests from the Internet to this service port will be redirected to the LAN server. Virtual Server function not only makes the users from Internet visit the local area network, but also keeps network security within the intranet as other services are still invisible from Internet. The LAN server must have a static or reserved IP Address because its IP Address may change when using the DHCP function.

Enable	IP	Internal Port	Service Port	Protocol
<input checked="" type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	TCP/UDP

Save Cancel

To use the virtual server:

Click **Add** in the table of Virtual Server.

Enter the **IP** Address of the PC providing the service application.

Enter the **Internal Port** number of the PC running the service application. You can leave it blank if the Internal Port is the same as the Service Port, or enter a specific port number.

Enter the numbers of external **Service Port**. You can type a service port or a range of service ports (the format is XXX – YYY, XXX is the start port, YYY is the end port). Internet users send request to the port for services.

Choose the one of the **protocols** used for this application: TCP, UDP, or TCP/UDP.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

Port Trigger

Check the **Enable** box to use the port trigger function. Due to the existence of the firewall, some applications such as online games, video conferences, VoIPs and P2P downloads need the device to configure the forwarding to work properly, and these applications require multiple ports connection, for single-port virtual server cannot meet the demand. Port trigger function comes at this time. When an application initiates a connection to the trigger port, all the incoming ports will open for subsequent connections.

Once configured, operation is as follows:

A local host makes an outgoing connection to an external host using a destination port number defined in the **Trigger Port** field.

The router records this connection, opens the incoming port or ports associated with this entry in the Port Triggering table, and associates them with the local host.

When necessary the external host will be able to connect to the local host using one of the ports defined in the **Incoming Port** field.

+	Add	⚙️	Edit	🗑️	Delete
<input type="checkbox"/>	Enable	Incoming Port	Trigger Port	Protocol	
<input checked="" type="checkbox"/>		<input type="text"/>	<input type="text"/>	TCP/UDP	
--	--	--	--	--	--
				Save	Cancel

To use the port trigger:

Click **Add** in the table of Port Trigger.

Enter the **Incoming Port** for incoming traffic. The port or port range is used by the remote system when it responds to the outgoing request. A response to one of these ports will be forwarded to the PC that triggered this rule. You can input at most 5 groups of ports (or port section). Every group of ports must be set apart with ",". For example, 2000-2038, 2050-2051, 2085, 3010-3030.

Enter the **trigger port** for outgoing traffic. An outgoing connection using this port will "Trigger" this rule.

Choose the one of the protocols used for this application: TCP, UDP, or TCP/UDP.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

UPnP

Check the **Enable** box to use the UPnP function. If you use applications such as multiplayer gaming, peer-to-peer connections, or real-time communications such as instant messaging or remote assistance (a feature in Windows XP), you should enable the UPnP function. The Universal Plug and Play (UPnP) function allows the devices, such as Internet computers, to access the local host resources or devices as needed. Host in the local area network can automatically open the corresponding ports on a router, and make the application of external host access the resources of the internal host through the opened ports. Therefore, the functions limited to the NAT can work properly. Compared to virtual server and port triggering, the application of UPnP doesn't need manual settings. It is more convenient for some applications required unfixed ports.

<input type="checkbox"/>	App Description	External Port	Internal Port	Protocol	IP Address	Status
--	--	--	--	--	--	--

- **App Description** – Displays the description provided by the application in the UPnP request.
- **External Port** – Displays the external port number that the router opened for the service application.
- **Protocol** - Displays which type of protocol is opened.
- **Internal Port** – Displays the internal service port number of the local host running the service application.
- **IP Address** - Displays the IP address of the local host which initiates the UPnP request.
- **Status - Enabled** means that port is still active. Otherwise, the port is inactive.

Security

The **Security** function is available only in **AP router** mode and **AP client router (WISP Client)** mode.

Stateful Packet Inspection (SPI) is a firewall that keeps track of the state of network connections (such as TCP streams, UDP communication) traveling across it. The firewall is programmed to distinguish legitimate packets for different types of connections. Only packets matching a known active connection will be allowed to pass through by the firewall and others will be rejected. SPI Firewall is enabled by factory default.

SPI Firewall

Check the **Enable** box to use the SPI Firewall function. If forwarding rules are enabled at the same time, the device will give priority to meet forwarding rules.

Ping

- **WAN Ping Forbidden:** The default setting is disabled. If enabled, the device will not reply the ping request originates from Internet.
- **LAN Ping Forbidden:** The default setting is disabled. If enabled, the device will not reply the ping request originates from local network.

VPN

A VPN is created by establishing a virtual point-to-point connection through the use of dedicated connections, virtual tunneling protocols, or traffic encryptions. Through VPN you can access your private network over Internet. A virtual private network connection across the Internet is similar to a wide area network (WAN) link between sites. From a user perspective, the extended network resources are accessed in the same way as resources available within the private network. When hosts in the local area network want to visit the remote virtual private network using virtual tunneling protocols, the corresponding VPN protocol should be enabled.

- **PPTP Passthrough** - PPTP (Point-to-Point Tunneling Protocol) allows the Point-to-Point Protocol (PPP) to be tunneled through an IP (Internet Protocol) network. Check the box to allow PPTP tunnels to pass through the Device.
 - **L2TP Passthrough** - L2TP (Layer Two Tunneling Protocol) is the method used to enable Point-to-Point connections via the Internet on the Layer Two level. Check the box to allow L2TP tunnels to pass through the Device.
 - **IPSec Passthrough** - IPSec (Internet Protocol security) is a suite of protocols for ensuring private, secure communications over IP (Internet Protocol) networks, through the use of cryptographic security services. Check the box to allow IPSec tunnels to pass through the Device.
-

DoS Protection

DoS (Denial of Service) Attack is to occupy the network bandwidth maliciously by the network attackers or the evil programs sending a lot of service requests to the Host, which incurs an abnormal service or even breakdown of the network. With DoS Protection function enabled, the device can analyze the specific fields of the IP packets and distinguish the malicious DoS attack packets. Upon detecting the packets, the device will discard the illegal packets directly and limit the transmission rate of the legal packets if the over legal packets may incur a breakdown of the network. The hosts sending these packets will be added into the **Blocked DoS Host List**. The device can defend a few types of DoS attack such as ICMP_FLOOD, UDP_FLOOD and TCP_SYN_FLOOD.

- **Packets Statistics Interval** - Select a value between 5 and 60 seconds from the drop-down list. The default value is 10. The value indicates the time interval of the packets statistics. The result of the statistic is used for analysis by ICMP-Flood, UDP Flood and TCP-SYN Flood.
- **ICMP_FLOOD Attack Filter** - Enter a value between 5 and 3600. The default value is 50. When the current ICMP-FLOOD Packets number is beyond the set value, the device will start up the blocking function immediately.
- **UDP_FLOOD Attack Filter** - Enter a value between 5 and 3600. The default value is 500. When the current UPD-FLOOD Packets number is beyond the set value, the device will start up the blocking function immediately.
- **TCP_SYN_FLOOD Attack Filter** - Enter a value between 5 and 3600. The default value is 50. When the current TCP-SYN-FLOOD Packets numbers is beyond the set value, the Device will start up the blocking function immediately.

Blocked DoS Host List

Click **Blocked DoS Host List** to display the blocked DoS host table including host IP and host MAC. Click **Refresh** to renewal the table list. Click **Clear** to release all the blocked hosts. If you want to release one or some of the blocked hosts, select them and Click **Unlock**.

Access Control

The function of **Access Control** is available only in **AP router** mode and **AP client router (WISP Client)** mode.

The function can be used to control the Internet activities of hosts in the local area network. For example, the online time limit and the specified web stations to visit can be controlled by the filtering policy.

Access Control ⌵

Access Control: Enable ?

Filtering Policy: Allow the packets specified by any enabled access control policy to pass through the device.
 Deny the packets specified by any enabled access control policy to pass through the device.

+ Add ⚙ Edit - Delete

	Enable	Protocol	Host IP	Target IP	Target Port	Days of a week	Time
--	--	--	--	--	--	--	--

Access Control

Check the **Enable** box to use the access control function.

Filtering Policy

There are two filtering policies to control the Internet activities:

- Allow the packets specified by any enabled access control policy to pass through the Device.

The hosts listed below are allowed to access the Internet under the rules. While others are forbidden to access.

- Deny the packets specified by any enabled access control policy to pass through the Device.

The hosts listed below are forbidden to access the Internet under the rules. While others are allowed to access.

Enable	Protocol	Host IP	Target IP	Target Port	Days of a week	Time
<input checked="" type="checkbox"/>	TCF				Sun,Mon,Tue,Wed,Th	00:00-24:00

Save Cancel

To use the access control:

Click **Add** in the table to create control rules.

Choose one of the protocols from the drop-down list used for the target, any of IP, TCP, UDP, or ICMP.

Enter the IP address or address range of the hosts that you need to control, for example 192.168.0.12-192.168.0.25.

Enter the IP address or address range of the targets that you need to control, for example 192.168.3.12-192.168.3.25.

Specify the port or port range for the target when protocol is TCP or UDP.

Select the certain day (days) for the rule.

Enter the time rule in HH:MM-HH:MM format, the default value is 00:00-24:00.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

Static Routing

The function of **Static Routing** is available only in **AP router** mode and **AP client router (WISP Client)** mode.

A static route is a pre-determined path that network information must travel to reach a specific host or network. If static route is used properly in the network, it can decrease the network overhead and improve the speed of forwarding packets.

Static routing is generally suitable for simple network environment, in which users clearly understand the topology of the network so as to set the routing information correctly. When the

network topology is complicated and users are not so familiar with the topology structure, this function should be used with caution or under the guidance of the experienced administrator.

Static Routing

Check the **Enable** box to use the static routing function.

To use the static routing:

Click **Add** to create a new static routing.

Enter the **Target Network IP**, the address of the network or host to be visited. The IP address cannot be on the same network segment with the device's WAN or LAN port.

Enter the Netmask.

Enter the **Gateway IP**, the address of the gateway that allows for contact between the Device and the network or host.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

Bandwidth Control

The function of **Bandwidth Control** is available only in **AP router** mode and **AP client router (WISP Client)** mode.

Bandwidth control function is used to control the Internet bandwidth in the local area network. In the case of insufficient bandwidth resources, enable the function to make the device allocate reasonable bandwidth to the clients and achieve the purpose of efficient use of the existing bandwidth. Via IP bandwidth control function, you can set the upper and lower limit in the bandwidth of the computer network and guarantee a smooth sharing network.

Total Ingress Bandwidth The total download speed limited through the WAN port. The maximum value is 100,000kbps.

Total Egress Bandwidth The total upload speed limited through the WAN port. The maximum value is 100,000kbps.

Bandwidth Control

Check the **Enable** box to use the bandwidth control function.

To use the bandwidth control:

Click **Add** in the table of bandwidth control.

Enter the **IP Range** of the target hosts which need to be controlled of bandwidth, for example 192.168.0.12-192.168.0.25.

Enter the **Port Range** through which the target hosts visit external server, for example 1-63258.

Choose one of the protocols used for this application: TCP, UDP, or TCP/UDP.

Enter the minimum ingress, maximum ingress, minimum egress and maximum egress of these IP addresses.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them.

IP&MAC Binding

We can effectively prevent ARP attack and IP embezzlement by enabling the IP&MAC binding. Within the local network, the device transmits IP packets to the certain target identified by the MAC address. Therefore, the IP and MAC address should be one-to-one correspondence and their corresponding relations are maintained by the ARP table. ARP attack can use forged information to renew the ARP table, and destroy the corresponding relations between IP and MAC addresses, which would prevent the communication between the device and the

corresponding host. When the IP&MAC Binding function is enabled, the IP and MAC relations in the ARP table won't be expired and renewed automatically, which effectively prevents the ARP attack.

Some functions such as access control and bandwidth control, are based on the IP addresses to identify the access clients. The network administrator can allocate every client a static IP, according to which he makes the access and bandwidth rules to control the clients' online behavior and the bandwidth they've used. Some illegal users may change the IP address in order to get higher Internet access. Enabling IP & MAC binding function can effectively prevent the IP embezzlement.

NOTE:

After IP&MAC binding function is enabled, the IP bound to the MAC cannot be used by other MACs. However this MAC can use other IPs within the same segment, which are not bounded by other MACs, to access the network.

IP&MAC Binding

Check the **Enable** box to use the IP&MAC binding function.

To use the IP&MAC Binding:

Click **Add** in the table of IP&MAC binding.


Enter the **IP** address and **MAC** address that you want to bind, for example 192.168.0.12, 00-23-5A-15-99-42. The new added entry is enabled by default.

Click **Save** after finishing the configuration.

Select the added entries, you can edit or delete them. Click **Import** to import all the entries in **Monitor > ARP Table**. The imported entries are disabled by default. You can select the certain entry and click **Edit** to enable it.

Chapter 6 Wireless Tab

On **Wireless** Tab, you can configure the related wireless parameters in different modes. Please selectively read the details according to the working mode of your device.



[About](#) [Support](#) [Log Out](#)

Operation Mode: Access Point Tools

QUICK SETUP
STATUS
NETWORK
WIRELESS
MANAGEMENT
SYSTEM

Basic Wireless Settings ⌵

Mode: 802.11a/n

Channel Width: 20/40MHz ?

Max TX Rate: MCS15 - 270/300 Mbps

Channel/Frequency: Auto ? Spectrum Analysis

Antenna Gain: 0 (0-30) dBi

Transmit Power: 23 dBm ?

MAXtream: Enable ?

MAXtream Station Mode: Auto Adjust ?

Apply

Wireless AP Settings ⌵

Wireless Radio: Enable

SSID: TP-LINK_Outdoor_BD205C Enable SSID Broadcast

Security Mode: None

RADIUS MAC Authentication: Enable ?

Apply

Multi-SSID ⌵

Wireless MAC Filtering ⌵

Advanced Wireless Settings ⌵

Distance Setting: 0 (0-200) km Auto (Only works within 0-27.9km) ?

Beacon Interval: 100 (40-1000)

RTS Threshold: 2346 (1-2346)

Fragmentation Threshold: 2346 (256-2346)

DTIM Interval: 1 (1-255)

AP Isolation: Enable

Short GI: Enable

Wi-Fi MultiMedia (WMM): Enable

QoS: Enable

Apply

If you have made any change of the parameters, click **Apply** to make the configuration take effect. There will be a blue bar at the top of the page to remind you to save the configuration. Click **Save Changes** when you finish all settings, otherwise all the settings will be recovered to last saved settings at reboot or power off.

You have unsaved changes. Would you like to save your changes?

Save

Wireless Basic Settings

This section allows you to configure wireless basic settings, such as 802.11 mode, Transmit Power, and data rates.

Basic Wireless Settings ⌵

Mode: ⌵

Channel Width: ⌵ ?

Max TX Rate: ⌵

Channel/Frequency: ⌵ ? Spectrum Analysis

Antenna Gain: (0-30) dBi

Transmit Power: 23 dBm ?

MAXtream: Enable ?

MAXtream Station Mode: ⌵ ?

Apply

Mode

Select the protocol standard used in the wireless network. With a frequency band of 2.4GHz, CPE210/CPE220/WBS210 supports five wireless modes: 802.11b, 802.11g, 802.11n, 802.11b/g and 802.11b/g/n. You are recommended to set the 11b/g/n mixed mode, and all of 802.11b, 802.11g and 802.11n wireless stations can connect to the device. CPE610/CPE510/CPE520/WBS510 has a frequency band of 5GHz, supporting 802.11a, 802.11n and 802.11a/n modes. We suggest to set in 11a/n mode, allowing both 802.11a and 802.11n wireless stations to access the device.

Channel Width

Select the channel width of this device. Options include 5MHz, 10MHz, 20MHz and 20/40MHz (this device automatically selects 20MHz or 40MHz, and 20MHz will be used if 40MHz is not available). Users select corresponding channel width according to whether their devices support it. According to IEEE 802.11n standard, using a channel width of 40MHz can increase wireless throughput. However, users may choose lower bandwidth due to the following reasons:

Increase the available number of channels within the limited total bandwidth.

To avoid interference from overlapping channels occupied by other devices in the environment.

Lower bandwidth can concentrate higher transmit power, increasing stability of wireless links over long distances.

Subject to the channel width of root AP in Client/ Bridge/ Repeater/ Client Router operation modes.

Max TX Rate

Set the maximum transmit data rate.

Channel/Frequency

Select the channel used by this device to improve wireless performance. 1/2412MHz refers to Channel 1 and the frequency is 2412MHz. This setting is only available in the modes of Access Point and AP Router.

CPE210/CPE220/WBS210 is a device with a frequency of 2.4GHz and CPE610/CPE510/CPE520/WBS510 has a frequency of 5GHz. We highly recommend you use the **Spectrum Analysis** tool to select a proper channel.

Antenna Gain

Antenna Gain is only available in the page of WBS products. Enter the antenna gain value according to the antennas and the value ranges from 0 to 30dBi.

The screenshot shows a configuration panel with three main sections:

- Channel/Frequency:** A dropdown menu set to 'Auto' with a help icon (?) and a 'Spectrum Analysis' button.
- Antenna Gain:** A text input field containing '0' with '(0-30)dBi' as a label.
- Transmit Power:** A slider control with a blue square marker and a text input field containing '3' with 'dBm' and a help icon (?) as labels.

Transmit Power

You can use the slider or manually enter the transmit power value. For WBS210 and WBS510, the maximum transmit power varies according to the antenna gain value.

NOTE: In most cases, it is unnecessary to select maximum transmit power. Selecting larger transmit power than needed may cause interference to neighborhood. Also it consumes more power and will reduce longevity of the device. Select a certain transmit power is enough to achieve the best performance. You can use the **Speed Test** tool to find the best performance.


MAXtream

This setting is only available in the modes of Access Point and AP Router. MAXtream is a proprietary technology of TP-Link for Wi-Fi system. It is based on TDMA (Time Division Multiple Access) so that data streams are transmitted in strict order. **MAXtream** aims to maximize throughput and minimize latency especially in a multi-STAs circumstance. "Hidden nodes" problem can also be eliminated with MAXtream enabled. We highly recommend you turn on MAXtream in a large scale wireless deployment to achieve better performance.

NOTE: MAXtream Technology is only compatible with Pharos series products. You cannot connect other Wi-Fi devices to an AP with MAXtream enabled.

MAXtream Station Mode

This setting is available in Client and Bridge mode and in the AP Client Router mode when the wireless AP settings is disabled.



For client devices connected to a root AP with MAXtream enabled, you can choose "Latency First" or "Throughput First" mode to better fit your application. For example, VoIP has a high demand for low latency. If you need a good experience for VoIP, you can select **Latency First**. Games and downloads ask for high throughput. You should select **Throughput First** to guarantee the high throughput for the games and downloads. Please choose **Auto Adjust** if you are not sure or you have no special requirements.

Wireless Client Settings

When this device is configured in the modes of Client, Repeater, Bridge and AP Client Router, the function of wireless client settings is available.

Wireless Client Settings ⌵

Wireless Radio: Enable

SSID of AP: Survey

Scan Range: Enable

MAC of AP: Lock to AP

WDS: ⌵

Security Mode: ⌵

Apply

SSID of AP

You can enter the SSID of the specific AP manually to connect to it or directly survey all the APs around by clicking **Survey**.

Scan Range	Check the Scan Range box and enter the scan range to make the device survey in the specified frequency range.
MAC of AP	Displays the MAC address of the root AP. It's possible that two or more networks use the same SSID in the AP list. Lock to AP can make the device connect to the specified AP you had connected before the next time.
WDS	<p>WDS (Wireless Distribution System) is a communication system among multiple wireless local area networks established between APs through wireless connection. In this system, only data frames with four address fields can be transparently forwarded at the link layer. In a WDS network, it is necessary that the root AP supports forwarding of data frames four address fields. If not, only data frames with the ARP/IP/PPPOE protocol can be forwarded among APs.</p> <ul style="list-style-type: none"> • Enable – Forward data frames to use four address fields. • Disable – Forward data frames to use three address fields. • Auto – The system automatically detects whether root device supports data frames with the format of three/four address fields, giving priority to the format of four address fields. The selection of Auto is recommended.
Security Mode	<p>Select the security mode of this device. To access the wireless network of root AP, the security mode should be set the same as that of root AP.</p> <ul style="list-style-type: none"> • None - Select this option if the root AP has no encryption. At the moment, it's no need to enter a password to access the wireless network of root AP. • WPA-PSK - Select this option if the security mode of the root AP is WPA-PSK. Enter the parameters including the version and encryption of WPA and PSK key, which must coincide with those of the root AP. • WPA – Select this option if the security mode of the root AP is WPA. Enter the parameters including the version, encryption, authentication, Phase 2 authentication, WPA user name and WPA user password, which must coincide with those of the root AP. • WEP - Select this option if the security mode of the root AP is WEP. Enter the parameters including authentication type, key format and WEP key, which must coincide with those of the root AP.

Wireless AP Settings

Wireless AP settings are only available in the modes of Access Point, Bridge, AP Router, and AP Client Router.

Wireless AP Settings

Wireless Radio: Enable

SSID: Enable SSID Broadcast

Security Mode: ▼

RADIUS MAC Authentication: Enable ?

Apply

Wireless Radio

Check the **Wireless Radio** box to enable this device to send and receive the wireless signal.

SSID

Enter a character string no more than 32 characters to name your wireless network. The default SSID is TP-Link_Outdoor_xxxxxx (xxxxxx is the last six characters of the MAC address of this device). We suggest you to set an easy-to-remember SSID to conveniently identify your wireless network.

Enable SSID Broadcast

With this option checked, AP will broadcast its SSID to hosts in the surrounding environment, as thus hosts can find the wireless network identified by this SSID. If SSID Broadcast is not enabled, hosts must enter the AP's SSID manually to connect to this AP.

Security Mode

Select the security mode of wireless network. This device provides four security modes: None, WPA (Wi-Fi Protected Access), WPA-PSK (WPA Pre-Shared Key) and WEP (Wired Equivalent Privacy). WPA-PSK is recommended. Settings vary in different security modes as the details in the following introduction.

Security Mode

You can select one of the following security modes:

1. **None:** If you want an open network without wireless security, select **none**. In this mode, network data is not encrypted, but you can still authenticate clients by enabling the RADIUS MAC Authentication function.

Wireless Radio: Enable

SSID: Enable SSID Broadcast

Security Mode: ▼

RADIUS MAC Authentication: Enable ?

Auth Server IP:

Auth Server Port:

Auth Server Key: Show

Accounting Server: Enable ?

RADIUS MAC Authentication

With this option checked, you can authenticate clients using their MAC addresses on your RADIUS authentication server.

Remember to log into your RADIUS authentication server and create authentication entries whose username and password are both the access-enabled clients' MAC address (for MAC address 11-22-33-AA-BB-CC, create an authentication entry whose username and password are both 112233aabbcc on the RADIUS server).

Authentication Server IP

Enter the IP address of the RADIUS authentication server.

Authentication Server Port

Enter the UDP port of the RADIUS authentication server. The most commonly used port is the default, 1812, but this may vary depending on the RADIUS authentication server you are using.

Authentication Server Key

Enter the shared key used between this device and the authentication server. The shared key is a case-sensitive text string used to validate communication between this device and the RADIUS authentication server. The shared key characters will be shown if you check the box of **show**.

Accounting Server

With this option checked, you can keep accounts on users using a RADIUS accounting server.

Accounting Server IP

Enter the IP address of the RADIUS accounting server.

Accounting Server Port

Enter the UDP port of the RADIUS accounting server. The most commonly used port is the default, 1813, but this may vary depending on the RADIUS accounting server you are using.

Accounting Server Key

Enter the password used between this device and the RADIUS accounting server. The shared key is a case-sensitive text string used to validate communication between this device and the RADIUS accounting server.

The shared key characters will be shown if you check the box of **show**.

- WPA-PSK:** Based on pre-shared key. It is characterized by higher safety and simple settings, which suits for common households and small business. **WPA-PSK** has two versions: WPA-PSK and WPA2-PSK.

Wireless Radio:	<input checked="" type="checkbox"/> Enable
SSID:	TP-LINK_Outdoor_886C84 <input checked="" type="checkbox"/> Enable SSID Broadcast
Security Mode:	WPA-PSK
Version:	Auto
Encryption:	Auto
PSK Password:	<input type="text"/> <input type="checkbox"/> Show
Group Key Update Period:	86400 seconds, 0 means no update

Version

Select one of the following versions:

- **Auto** –Select WPA or WPA2 automatically based on the wireless station's capability and request.
- **WPA** –Pre-shared key of WPA.
- **WPA2** –Pre-shared key of WPA2.

Encryption

Select the Encryption type, including Auto, TKIP and AES. The default setting is Auto, which can select TKIP (Temporal Key Integrity Protocol) or AES (Advanced Encryption Standard) automatically based on the wireless station's capability and request. AES is more secure than TKIP and **TKIP** is not supported in 802.11n mode. We recommend you select AES as the encryption type.

PSK Password

Configure the WPA-PSK/WPA2-PSK password with ASCII or Hexadecimal characters. For ASCII, the length should be between 8 and 63 characters with combination of numbers, letters (case-sensitive) and common punctuations; for Hexadecimal, the length should be 64 characters (case-insensitive, 0-9, a-f, A-F).

Group Key Update Period

Specify the group key update period in seconds. The value can be either 0 or at least 30, 0 means no update.

3. **WPA:** Based on RADIUS Server, WPA can assign different password for different users and it is much safer than WPA-PSK. However, its maintenance costs much which is only suitable for enterprise users. At present, WPA has two versions: WPA and WPA2.

Wireless Radio:	<input checked="" type="checkbox"/> Enable
SSID:	TP-LINK_Outdoor_BD205C <input checked="" type="checkbox"/> Enable SSID Broadcast
Security Mode:	WPA
Version:	Auto
Encryption:	Auto
Authentication Server IP:	0.0.0.0
Authentication Server Port:	1812
Authentication Server Key:	<input type="text"/> <input type="checkbox"/> Show
Group Key Update Period:	0 seconds. (0 means no update.)
Accounting Server:	<input checked="" type="checkbox"/> Enable ?
Accounting Server IP:	0.0.0.0
Accounting Server Port:	1813
Accounting Server Key:	<input type="text"/> <input type="checkbox"/> Show

Version

Select one of the following versions:

- **Auto** –Select WPA or WPA2 automatically based on the wireless station's capability and request.
- **WPA** –Pre-shared key of WPA.
- **WPA2** –Pre-shred key of WPA2.

Encryption

Select the Encryption type, including Auto, TKIP, and AES. The default setting is Auto, which can select TKIP (Temporal Key Integrity Protocol) or AES (Advanced Encryption Standard) automatically based on the wireless station's capability and request. AES is more secure than TKIP and TKIP is not supported in 802.11n mode. We recommend you select AES as the encryption type.

Authentication Server IP

Enter the IP address of the RADIUS authentication server.

Authentication Server Port

Enter the UDP port of the RADIUS authentication server. The most commonly used port is the default, 1812, but this may vary depending on the RADIUS authentication server you are using.

Authentication Server Key

Enter the shared key used between this device and the RADIUS authentication server. The shared key is a case-sensitive text string used to validate communication between this device and the RADIUS authentication server.

The shared key characters will be shown if you check the box of **show**.

Group Key Update Period

Specify the group key update period in seconds. The value can be either 0 or at least 30, 0 means no update.

Accounting Server With this option checked, you can keep accounts on users using a RADIUS accounting server.

Accounting Server IP Enter the IP address of the RADIUS accounting server.

Accounting Server Port Enter the UDP port of the RADIUS accounting server. The most commonly used port is the default, 1813, but this may vary depending on the RADIUS accounting server you are using.

Accounting Server Key Enter the password used between this device and the RADIUS accounting server. The shared key is a case-sensitive text string used to validate communication between this device and the RADIUS accounting server.

The shared key characters will be shown if you check the box of **show**.

4. **WEP:** Based on the IEEE 802.11 standard, this encryption is less safe than the above two modes. The **WEP** are not supported in 802.11n mode.

The screenshot shows a configuration window for wireless security. At the top, 'Wireless Radio' is checked and set to 'Enable'. Below it, the 'SSID' is 'TP-LINK_Outdoor_886C84' and 'Enable SSID Broadcast' is checked. The 'Security Mode' is set to 'WEP'. Underneath, 'Auth Type' is 'Auto' and 'Key Format' is 'Hex'. There are four 'Key Selected' options: 'Key 1' (selected with a radio button), 'Key 2', 'Key 3', and 'Key 4'. Each key has a corresponding 'WEP Key' input field. To the right, 'Key Type' is set to 'Disabled' for all four keys.

Auth Type Select the Auth type of the WEP security on the drop-down list. The default setting is Auto, which can select Open System or Shared Key authentication type automatically based on the wireless station's capability and request.

Key Format Select **Hex** or **ASCII**. Hexadecimal format stands for any combination of hexadecimal digits (0-9, a-f, A-F) in the specified length. ASCII format stands for any combination of keyboard characters in the specified length.

Key Selected You can configure four keys in advance and select the present valid key.

WEP Key Enter the WEP keys. The length and valid characters of the key are affected by key type.

Key Type

Select the WEP key length (64-bit, or 128-bit, or 152-bit) for encryption. **Disabled** means this WEP key is not used.

- **64bit** -You can enter 10 hexadecimal digits (any combination of 0-9, a-f, A-F, and null key is not permitted) or 5 ASCII characters.
- **128bit** -You can enter 26 hexadecimal digits (any combination of 0-9, a-f, A-F, and null key is not permitted) or 13 ASCII characters.
- **152bit** -You can enter 32 hexadecimal digits (any combination of 0-9, a-f, A-F, and null key is not permitted) or 16 ASCII characters.

Multi-SSID

Multi-SSID is only available in Access Point mode.

This device can build up to four virtual wireless networks for users to access. When the Multi-SSID function of the device is enabled, its VLAN function is enabled at the same time. It can work together with switches supporting 802.1 Q VLAN and supports maximum four VLANs. The device adds different VLAN tag to the clients which connect to the corresponding wireless network. The clients with different VLAN ID cannot directly communicate with each other.

Clients connected to the device via cable don't belong to any VLAN. Thus wired client can communicate with all the wireless clients despite the VLAN settings.

Multi-SSID ⌵

Multi-SSID: Enable

+ Add ⚙ Edit - Delete

Enable	SSID	VLAN	SSID Broadcast	AP Isolation
<input checked="" type="checkbox"/>	TP-LINK_Outdoor_886C84	1	Enable	Disable

Security Settings

SSID:

Security Mode:

Multi-SSID

Check the **Enable** box to use the Multi-SSID function.

Enable	SSID	VLAN	SSID Broadcast	AP Isolation
<input checked="" type="checkbox"/>	TP-LINK_Outdoor_886C84	1	Enable	Disable
<input checked="" type="checkbox"/>	ABC	2	Enable	Enable

OK Cancel

Click **Add** in the table of Multi-SSID.

Create a wireless network name (**SSID**), a string from 1 to 32 characters.

Set the **VLAN** ID of wireless network identified by this SSID, and the value ranges from 1 to 4094.

Select whether to broadcast this SSID or not.

Enable **AP Isolation**, the device would isolate the hosts within the same wireless network. All the hosts cannot communicate with each other. The default setting is **Disable**.

SSID

Select the added SSID to configure its security mode.

Security Mode

If all the hosts are allowed to access the wireless network, select **None**. For the safety of wireless network, you are suggested to encrypt your wireless network. This device provides three security modes: WPA-PSK (Pre-Shared Key), WPA (Wi-Fi Protected Access) and WEP (Wired Equivalent Privacy). WPA-PSK is recommended. Please refer to **Security Mode** in the Wireless AP Settings section for further information.

Wireless MAC Filtering

Wireless MAC Filtering function uses MAC addresses to determine whether one host can access the wireless network or not. Thereby it can effectively control the user access in the wireless network. This function is available in all modes except the client mode.

Wireless MAC Filtering

Wireless MAC Filtering: Enable

Filtering Rules:

Deny the stations specified by any enabled entries in the list to access the network.

Allow the stations specified by any enabled entries in the list to access the network.

Enable	SSID	MAC	Comment
<input checked="" type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
--	--	--	--

Save Cancel

Apply

Wireless MAC Filtering Check the **Enable** box to use wireless MAC filtering function.

Enable	SSID	MAC	Comment
<input checked="" type="checkbox"/>			
--	--	--	--

Save Cancel

Click **Add** in the table of wireless MAC filtering.

Select the wireless network (**SSID**) that you need to filter. In AP mode, if Multi-SSID is enabled, you should set different filtering rules for each SSID.

Enter the **MAC** address of the wireless host that you need to filter.

Enter the description information of this filtering rule in the **Comment** field.

Filtering Rules

There are two filtering policies to control the MAC filtering:

- Allow the stations specified by any enabled entries in the list to access.
The stations listed below are allowed to access the wireless network under the rules. While others are forbidden to access.
- Deny the stations specified by any enabled entries in the list to access.
The stations listed below are forbidden to access the wireless network under the rules. While others are allowed to access.

The stations listed below are forbidden to access the wireless network under the rules. While others are allowed to access.

Wireless Advanced Settings

Wireless Advanced Settings

Distance Setting: (0-200)km Auto (Only works within 0-55.8km) ?

Beacon Interval: (40-1000)

RTS Threshold: (1-2346)

Fragmentation Threshold: (256-2346)

DTIM Interval: (1-255)

AP Isolation: Enable

Short GI: Enable

Wi-Fi MultiMedia (WMM): Enable

QoS: Enable

Apply

Distance Setting

Specify the distance between AP and Station. If this device serves as a client, the value is the distance between this device and the root AP. If this device serves as an AP, the value is the distance between the farthest client and this AP.

You can manually enter the value or enable the Auto option.

Manual: Enter the distance manually in the input box. The value is limited to 0-200km, and we recommend you set the value to 110% of the real distance.

Auto (Only works within 0-xx km): Check the Auto option, then the system will dynamically detect the distance. This function is available only when the distance is less than xx kilometers. The value xx varies according to the channel width you set. CPE210 does not support this option.

The distance value will be converted to a corresponding ACK timeout value, and the ACK timeout value will influence the throughput performance to a large extent.

Suppose device A is sending data frames to device B. Every time device A sends a data frame, it waits for the ACK frame from device B. If the ACK frame arrives within the ACK timeout, device A will send the next data frame. Otherwise, device A will re-send the data frame. The throughput performance drops either if too many data frames are re-sent (the ACK timeout is too short) or if device A waits too long to send the next data frame (the ACK timeout is too long). Therefore, a proper distance value determines an appropriate timeout value, which would greatly improve the throughput performance.

Beacon Interval

Beacons are transmitted periodically by the device to announce the presence of a Wireless network for the clients. Beacon Interval value determines the time interval of the beacons sent by the device. You can specify a value from 40 to 1,000. The default value is 100.

RTS Threshold

When the RTS threshold is activated, all the stations and APs follow the Request to Send (RTS) protocol. When the station is to send packets, it will send a RTS to AP to inform the AP that it will send data. After receiving the RTS, the AP notice other stations in the same wireless network to delay their transmitting of data. At the same time, the AP inform the requesting station to send data. The value range is from 0 to 2346 bytes. The default value is 2346, which means that RTS is disabled.

Fragmentation Threshold

Specify the fragmentation threshold for packets. If the size of the packet is larger than the fragmentation threshold, the packet will be fragmented into several packets. Too low fragmentation threshold may result in poor wireless performance caused by the excessive packets. The recommended and default value is 2346 bytes.

DTIM Interval

This value indicates the number of beacon intervals between successive Delivery Traffic Indication Messages (DTIMs) and this number is included in each Beacon frame. A DTIM is contained in Beacon frames to indicate whether the access point has buffered broadcast and/or multicast data for the client devices. Following a Beacon frame containing a DTIM, the access point will release the buffered broadcast and/or multicast data, if any exists. You can specify the value between 1-255 Beacon Intervals. The default value is 1, indicating the DTIM Interval is the same as Beacon Interval. An excessive DTIM interval may reduce the performance of multicast applications. We recommend you keep it by default.

AP Isolation

With this option enabled, AP Isolation to isolate all wireless stations connected to this device so that they cannot communicate with each other. This function will be disabled if WDS/Bridge is enabled.

Short GI

Short GI is used to increase the throughput by reducing the guard interval time. We recommend you enable this function.

Wi-Fi MultiMedia (WMM)

With WMM enabled, the system will prioritize traffic according to the data type when forwarding data. Time-dependent traffic, such as video or audio packets, gets a higher priority than normal traffic.


We recommend you enable this function when you are running the video or audio application.

QoS

The QoS function improves the transmission performance of video or audio traffic by optimizing the scheduling policy between the AP and the clients.

Chapter 7 Management Tab

On **Management** Tab, you can configure system management services: System Log, Miscellaneous, Ping Watch Dog, and Dynamic Domain Name System (DDNS). Web server, Simple Network Management Protocol (SNMP), SSH server, RSSI LED Thresholds are also available.


About Support Log Out

Operation Mode: Access Point
Tools ▼

QUICK SETUP
STATUS
NETWORK
WIRELESS
MANAGEMENT
SYSTEM

System Log

Open System Log: Open

Download to PC: Download

Auto Mail Settings: Setting

Auto Mail Feature: Disabled

Miscellaneous

Discovery: Enable ?

CDP: Enable ?

Apply

Ping Watch Dog

Ping Watch Dog: Enable

IP Address To Ping:

Ping Interval: (10-300) seconds

Startup Delay: (60-300) seconds

Fail Count To Reboot: (1-65535)

Apply

Dynamic DNS

Service Provider: Dyn dns (www.dyndns.com) ▼

Dynamic DNS: Enable

User Name:

Password: Show

Domain Name:

Connection Status: Not launching.

Login
Logout

Apply

Web Server

Secure Connection (HTTPS): Enable

Secure Server Port:

Server Port:

Remote Login IP Address: ?

Session Timeout: minutes

MAC Authentication: Enable

MAC1:

MAC2:

MAC3:

MAC4: Add PC's MAC

Apply

SNMP Agent

SNMP Agent: Enable

SysContact:

SysName:

SysLocation:

Get Community:

Get Source:

Set Community:

Set Source:

Apply

SSH Server

Server Port:

SSH Login: Enable

Remote Management: Enable ?

Apply

RSSI LED Thresholds

	LED1	LED2	LED3	LED4
Thresholds (dBm):	<input type="text" value="-94"/>	<input type="text" value="-80"/>	<input type="text" value="-73"/>	<input type="text" value="-65"/>

Apply

If you have made any change of the parameters, click **Apply** to make the configuration take effect. There will be a blue bar at the top of the page to remind you to save the configuration. Click **Save Changes** when you finish all settings, otherwise all the settings will be recovered to last saved settings at reboot or power off.

You have unsaved changes, would you like to save now?

Save Changes

System Log

System logs record the events and activities while the router is running. If a failure happens on the router, System logs can help to diagnose the issue.

System Log

Open System Log:

Download to PC:

Auto Mail Setting:

Auto Mail Feature: Disabled

Open System Log

Check system log by clicking **Open** and then appears the following popup page.

System Log				
Index	Time	Type	Level	Message
1	2015-01-01 00:00:05	OTHER	INFO	System started
2	2015-01-01 00:00:16	OTHER	WARNING	LAN IP and mask changed to 192.168.0.254 255.255.255.0

This page displays detailed system logs that can be sorted on columns by ascending or descending order. Columns can be chosen from Time, Type, Level, and Message.

Download to PC

Enables users to download system logs to PC.

Auto Mail Setting

Enables users to mail system logs automatically. Click **Setting** and the following page appears.

Set the receiving and sending mailbox address, server address, validation information as well as the timetable for Auto Mail Feature.

- **From** – Enter sender's mail box address.
- **To** – Enter the recipient's address.
- **SMTP Server** – Enter sender's SMTP server.
- **Authentication** - Most SMTP Server requires Authentication.
- **User Name** – Sender's mail account name.
- **Password** – Sender's mail account password.
- **Confirm Password** –Re-enter your mail account password.

Check **Auto Mail Feature** box, you can set the device how and when to send the log to the specified mailbox.

Miscellaneous

Discovery

Enable the function to let TP-Link Pharos Control software discover the device. With its main function to centralize monitoring and managing network devices in the network platform, Pharos Control is network management software developed independently by TP-Link and it currently supports Pharos series products.

CDP

With this function enabled, this device can share its information with the neighboring devices that support CDP (Cisco Discovery Protocol, a device discovery protocol developed by Cisco).

Ping Watch Dog

Ping Watch Dog sets the device to continuously ping a user-defined IP address (it can be the Internet gateway, for example) to check the network connectivity. If there is a connection failure then the device will automatically reboot.

Ping Watch Dog is dedicated to continuously monitoring the connectivity to a specific host using the Ping tool. The Ping tool sends ICMP echo request packets to the target host and listens for ICMP echo response. If the defined number of replies is not received, the tool reboots the device.

Ping Watch Dog

Ping Watch Dog: Enable

IP Address To Ping:

Ping Interval: (10-300)seconds

Startup Delay: (60-300)seconds

Fail Count To Reboot: (1-65535)

Apply

Ping Watch Dog

Check the **Enable** box to use the function of Ping Watch Dog.

IP Address To Ping

Specify the IP address of the target host to which the Ping Watch Dog Utility will send ping packets.

Ping Interval

Enter the time interval (in seconds) between two successive ping packets. The default value is 300 seconds.

Startup Delay

Enter the initial time delay (in seconds) from device startup to the first ICMP echo requests sent by Ping Watch Dog. The default value is 300 seconds.

The Startup Delay value should be at least 60 seconds as the device's initialization takes a considerable amount of time.

Failure Count To Reboot

Enter the fail count of ICMP echo request. If the device sends the specified count of ICMP echo requests to the host and none of the corresponding ICMP echo response packets is received, Ping Watch Dog will reboot the device. The default value is 3.


Dynamic DNS

The main function of Dynamic DNS (DDNS) is mapping the fixed domain name to dynamic IP address.

When a device connects to the Internet through PPPoE or Dynamic IP, the WAN IP address it gets is not fixed, which is inconvenient for the Internet users to access the servers in the local area network through IP address. Dynamic DNS function allows users to access servers using a fixed domain name.

The DDNS server will establish a mapping table about the dynamic IP address and the fixed domain name. When the WAN IP address of the device changes, it will make an update request to the specified DDNS server, and then the DDNS server will update the mapping relation between the IP address and the domain name. Therefore, whenever the WAN IP address changes, users on the Internet can still access the servers in the local area network using a fixed, easy-to-remember domain name.

The DDNS function that serves as the client of DDNS service must work with DDNS server. Please register an account to DDNS service provider (NO-IP, Dyndns or Comexe) before using this function.



The screenshot shows a web interface titled "Dynamic DNS". It contains the following elements:

- Service Provider:** A dropdown menu currently set to "No-IP (www.no-ip.com)".
- Dynamic DNS:** A checkbox labeled "Enable" which is currently unchecked.
- User Name:** A text input field.
- Password:** A text input field with a "Show" checkbox to its right.
- Domain Name:** A text input field.
- Connection Status:** A label that reads "Not launching!".
- Buttons:** "Login" and "Logout" buttons are positioned below the status, and an "Apply" button is located at the bottom right of the form area.

Service Provider

Select your DDNS service provider from the available DDNS service providers including NO-IP (www.no-ip.com), Dyndns (www.dyndns.com) and Comexe (www.comexe.net).

Dynamic DNS

Check the **Enable** box to use the function.

- **User Name** - Enter the user name of the DDNS account.
- **Password** - Enter the password of the DDNS account.
- **Show** - Check the box to display the password characters.
- **Domain Name** -Enter a customized domain name. Even if your IP is dynamic, other users on the Internet can still access your server via this fixed domain name after enabling the DDNS function.
- **Connection Status** -Displays the connection status between this device and the DDNS server.

Web Server

The Web Server function enables users to log in to the web management page to manage this device remotely over the Internet.

Secure Connection (HTTPS)

The Secure Connection (HTTPS) mode is enabled by default.

Secure Server Port

Specify the server port that the Web server uses in the Secure Connection (HTTPS) mode, and the default is 443.

Server Port

Specify the server port that the Web server uses in the HTTP mode, and the default is 80.

Remote Login IP Address

Configure the IP address that can remotely visit the web management page of this device. Enter 0.0.0.0 to forbid any remote IP's login. Enter 255.255.255.255 to allow all the remote IP to visit.

Session Timeout

Enter the maximum timeout before the session expires. Once a session expires, you must log in again using the username and password.

MAC Authentication

Enable this function to allow PCs with specific MAC addresses to access the web management page. And then enter each MAC address in the MAC field. The format for the MAC addresses is XX-XX-XX-XX-XX-XX. Only the PCs with the MAC addresses listed can use the password to access the device's web management page and the others will be blocked. By default, the function is not enabled. All the PCs in the local area network are allowed to access the device's web management page.

Click **Add PC's MAC**, your PC's MAC address will be added in the list above. Click **Apply** to save your settings.

SNMP Agent

You can get the traffic information and transmit condition by using the SNMP Agent function.

Simple Network Management Protocol (SNMP) is an application layer protocol that facilitates the exchange of management information between network devices. Main functions of SNMP include monitoring network performance, detecting and analyzing network error, configuring network devices, and so on. Under the circumstance of network working normally, SNMP can play a part in statistics, configuration and testing. When networks have troubles, SNMP can detect and restore these troubles.

Configuring this device as SNMP Agent, it can receive and process the management message from the network management system.

SNMP Agent

SNMP Agent: Enable

SysContact:

SysName:

SysLocation:

Get Community:

Get Source:

Set Community:

Set Source:

SNMP Agent	Enable the SNMP Agent function and the SNMP Agent will gather the information of this device and respond to information requests from one or more management systems.
SysContact	Enter the information of the contact person for this managed node.
SysName	Enter an administratively-assigned name for this managed node.
SysLocation	Enter the physical location of this managed node.
Get Community	Community refers to a host group aiming at network management. Get Community only has the read-only right of the device's SNMP information. The get community name can be considered as a password used to restrict the access right of SMNP managers. The default name is public.
Get Source	Defines the IP address (for example, 10.10.10.1) or subnet (for example, 10.10.10.0/24) for management systems that can serve as Get Community to read the SNMP information of this device. The default is 0.0.0.0, which means all hosts can read the SNMP information of this device.
Set Community	Set Community has the read and write right of the device's SNMP information. Enter the community name that allows read/write access to the device's SNMP information. The community name can be considered as a password to restrict the access right of SNMP managers. The default name is private.
Set Source	Defines the IP address (for example, 10.10.10.1) or subnet (for example, 10.10.10.0/24) for management systems that can serve as Set Community to read and write the SNMP information of this device. The default is 0.0.0.0, which means all hosts can read and write the SNMP information of this device.

NOTE:

Defining community can allow management systems in the same community to communicate with the SNMP Agent. The community name can be seen as the shared password of the network hosts group. Thus, for the safety, we suggest modifying the default community name before enabling the SNMP Agent service. If the field of community is blank, the SNMP Agent will not respond to any community name.

SSH Server

The SSH Server function allows users to log in and manage the device through SSH connection on the SSH client software.

SSH (Secure Shell) is a security protocol established on application and transport layers. SSH-encrypted-connection is similar to a telnet connection, but essentially the old telnet remote management method is not safe, because the password and data transmitted with plain-text can be easily intercepted. SSH can provide information security and powerful authentication when you log in this device remotely through an insecure network environment. It can encrypt all the transmission data and prevent the information in remote management from being leaked.

Server Port

Enter the TCP/IP port of the SSH Server. The default port is 22.

SSH Login

Enable the SSH Server function.

Remote Management

Enable the function to let TP-Link Pharos Control software manage the device remotely.

RSSI LED Thresholds

You can configure the LEDs on the device to light up when received signal levels reach the values defined in the following fields. This allows a technician to easily deploy a Pharos series product without logging into the device (for example, for antenna alignment operation).

NOTE:

CPE610 does not support this feature.

Thresholds (dBm)

The specified LED will light up if the signal strength reaches the values in the field. For example, if the signal strength fluctuates around -63 dBm, then the LED threshold values can be set to the following: -70, -65, -62, and -60. The default values are set according to the verified optimum values. We recommend you keep it by default.

The default LED threshold values may vary among different product models in terms of radio features. The figure above shows the default values of CPE210.

Chapter 8 System Tab

The **System** Tab controls system maintenance routines, device customization, location management, user account management, firmware update, time setting and configuration backup.

The screenshot shows the TP-Link PHAROS web interface. At the top, there is a navigation bar with the TP-Link logo and 'PHAROS' text. To the right, there are links for 'About', 'Support', and 'Log Out'. Below this, the 'Operation Mode' is set to 'Access Point' and 'Tools' is selected. The main navigation tabs are 'QUICK SETUP', 'STATUS', 'NETWORK', 'WIRELESS', 'MANAGEMENT', and 'SYSTEM', with 'SYSTEM' being the active tab.

The 'SYSTEM' tab is divided into several sections:

- Device:** Includes 'Device Name' (CPE510) and 'Language' (English) fields, with an 'Apply' button.
- Location:** Includes 'Longitude' (0) and 'Latitude' (0) fields, with an 'Apply' button.
- User Account:** Includes 'Current User Name' (admin), 'Current Password', 'New User Name', 'New Password', and 'Confirm New Password' fields, with 'Show' checkboxes and an 'Apply' button.
- Time Setting:** Includes 'Time Zone' ((GMT+08:00) Beijing, Urumqi, Hong), 'Date' (2015/01/01), 'Time' (00:39:18), 'NTP Server 1', and 'NTP Server 2' fields. It also has 'Get GMT', 'Synchronize with PC's Clock', and 'Daylight Saving Time' (Setting) options, with an 'Apply' button.
- Firmware Update:** Shows 'Firmware Version: 2.1.0 Build 20170609 Rel. 57434 (0000)' and an 'Upload Firmware' field with 'Browse' and 'Upload' buttons.
- Configuration:** Includes 'Backup Configuration' (Backup), 'Upload Configuration' (Browse, Upload), 'Reset to Factory Defaults' (Reset), and 'Reboot Device' (Reboot) buttons.

If you have made any change of the parameters, click **Apply** to make the configuration take effect. There will be a blue bar at the top of the page to remind you to save the configuration. Click **Save Changes** when you finish all settings, otherwise all the settings will be recovered to last saved settings at reboot or power off.

You have unsaved changes. Would you like to save your changes?

Save

Device

The Device Name is the model of device by default. You can customize a new personal and easy-to-remember name.

Device Name Customize the name of the device.

Language Displays the default language in the web management page is English.

Location

Longitude and latitude define the device's coordinates.

Longitude Enter the longitude of the device's location in decimal degree. The positive number indicates the east longitude while the negative number indicates the west longitude.

Latitude Enter the latitude of the device's location in decimal degree. The positive number indicates the north latitude while the negative number indicates the south latitude.

User Account

You can change the user password to protect your device from unauthorized login. We recommend that you change the default user password on the very first system setup.

User Account

Current User Name:

Current Password: Show

New User Name:

New Password: Show

Confirm New Password:

Current User Name Displays the current user name.

Current Password Enter the current password for the user account. Check the **Show** box to display what you've entered.

New User Name Enter the new user name for the user account.

New Password Enter the new password for the user account. Check the **Show** box to display what you've entered.

Confirm New Password Re-enter the new password for the user account.

NOTE:

The password is a string from 1 to 15 alphanumeric characters or symbols.

Time Setting

Time Setting

Time Zone: ▾

Date:

Time: ▾

NTP Server 1:

NTP Server 2:

Daylight Saving Time:

Time Zone Select your local time zone from the drop-down list.

Date	Specify the device's date. Click the calendar icon or manually enter the date in the following format: YYYY/MM/DD. For example, for November 25, 2013, enter 2013/11/25 in the field.
Time	Specify the device's date. Select the time from the drop-down list or manually enter the date in HH:MM:SS format.
NTP Server 1	Enter the primary NTP Sever address.
NTP Server 2	Enter an alternative NTP Server address.
Get GMT	Click Get GMT to get GMT from the NTP server.
Synchronize with PC's Clock	Date and time of the device can be synced with your PC's system time.
Daylight Saving Time	Click Setting to set the daylight saving time on the following page.

Daylight Saving Time

Daylight Saving Time
✕

DST Status: Enable

Predefined Mode

USA
 European
 Australia
 New Zealand

Recurring Mode

Time Offset: minutes

Start Time: Last ▾ in in at :

End Time: Last ▾ in in at :

Date Mode

Time Offset: minutes

Start Time: - - at :

End Time: - - at :

Apply

DST Status Check the **Enable** box to use the function.

Predefined Mode

Select a predefined DST configuration.

- **USA:** Second Sunday in March, 02:00 ~ First Sunday in November, 02:00.
- **European:** Last Sunday in March, 01:00 ~ Last Sunday in October, 01:00.
- **Australia:** First Sunday in October, 02:00 ~ First Sunday in April, 03:00.
- **New Zealand:** Last Sunday in September, 02:00 ~ First Sunday in April, 03:00.

Recurring Mode

Specify the DST configuration in recurring mode. This configuration is recurring in use.

- **Time Offset:** Specify the time offset in minutes when Daylight Saving Time comes.
- **Start/End Time:** Select the start time and end time of Daylight Saving Time. The start time is the standard time, and the end time is the Daylight Saving Time.

Date Mode

Specify the DST configuration in Date mode. This configuration is one-off in use.

- **Time Offset:** Specify the time adding in minutes when Daylight Saving Time comes.
- **Start/End Time:** Select the start time and end time of Daylight Saving Time. The start time is the standard time, and the end time is the Daylight Saving Time.

NOTE:

When the DST is enabled, the default daylight saving time is European in predefined mode.

Firmware Update

Firmware update can improve the function of the device.

Firmware Update	
Firmware Version: 2.1.0 Build 20170609 Rel. 57434 (0000)	
Upload Firmware:	<input type="text"/> <input type="button" value="Browse"/> <input type="button" value="Upload"/>

Firmware version

Displays the current firmware version.

Upload Firmware

Please visit TP-Link website www.tp-link.com/en/support/download/ to download the latest firmware. The system configuration can be preserved while the device is updated with a new firmware version. However, we recommend that you back up current system configuration before updating the firmware. Firmware update takes three steps:

Click **Browse** to locate the new firmware file.

Select the file and click **Open**. The new firmware to be uploaded is displayed in the field.

Click **Upload** and there will be a pop-up page which gives you three options of keeping your configurations or restoring to factory default after the upgrade or just cancel the upgrade.

NOTE:

Please select the proper software version that matches your hardware to upgrade.

To avoid damage, please do not power off the device while upgrading.

After upgrading, the device will reboot automatically.

Configuration

The controls in this section manage the device configuration routines and the option to reset the device to factory default settings.

The device configuration is stored in the plain text file. You can back up, restore, or update the system configuration file.

Configuration

Backup Configuration:

Upload Configuration:

Reset to Factory Defaults:

Reboot Device:

Backup Configuration

Click **Backup** to back up the current system configuration file.

Upload Configuration

Click **Browse** to locate the new configuration file. Select the file and click **Open**, then the new configuration to be uploaded is displayed in the field. Click **Upload** to upload the new configuration to the device. We recommend that you back up your current system configuration before uploading the new configuration.

Reset to Factory Defaults

Resets the device to the default settings. This option will reboot the device, and all factory default settings will be restored. It's recommended that you back up your current system configuration before resetting the device to its defaults.

Reboot Device

Initiates a full reboot cycle of the device. The system configuration stays the same after the reboot cycle completes. Any changes that have not been applied will be lost.

NOTE:


After backing up, the device will reboot automatically.

To avoid damage, please don't turn off the device while uploading.

You are suggested to back up the configuration before upgrading.

Chapter 9 Tools List

This device provides some useful tools including Ping, Traceroute, Speed Test, Survey and Spectrum Analysis.



Ping

Ping test function is used to test the connectivity and reachability between the device and the target host so as to locate the network malfunctions.

Ping Watch Dog ✕

Destination IP/Domain:

Packet Count: (1-50)

Ping Timeout: (100-2000) milliseconds

Packet Size: (4-1472) bytes

Ping Results

Ping 192.168.0.1 with 64 bytes of data:

Requests timed out.

Requests timed out.

Requests timed out.

Requests timed out.

Destination IP/Domain

Enter the IP address of the destination node for Ping test. Click **Start**, the device will send Ping packets to test the network connectivity and reachability of the host and the results will be displayed in the list below.

Packet Count

Enter the number of packets to be sent during the testing. It can be 1 to 50 and the default is 4.

Ping Timeout

Enter a time value to wait for a response. It can be 100-2000 milliseconds. The default value is 800 milliseconds.

Packet Size

Enter the number of data bytes to be sent. It can be 4-1472 bytes and the default is 64.

Traceroute

Traceroute function is used to tracks the route packets taken from source on their way to a given target host. When malfunctions occur in the network, you can troubleshooting with traceroute utility.

Destination IP/Domain

Enter the destination IP address or the Domain name. Click **Start**, the device will send Tracert packets to the target host and the results will be displayed in the list below.

Traceroute Max TTL

Set the maximum number of hops (max TTL to be reached) in the path to reach the target (destination). The default is 5.

Speed Test

Speed Test tool is used for testing the throughput between two Pharos products in the same network. The test requires one of the two devices to be set as a server and the other as a client. The client launches the test request to the server and the server respond to it. The test result will display on the page of the client.

Speed Test

RX: null TX: null Total: null

Client Server

Server IP:

Direction: unidirectional (RX) ▼

Testing:

Start

Test Result	Displays the data streams that the device is transmitting (TX), receiving (RX) and both of them (Total).
Client	The side to initiatively launch the test request. The client side can configure parameters including server's IP and direction.
Server	The side to passively accept the test request.
Server IP	The IP address of the server.
Direction	Select the direction of the speed test including unidirectional (RX) , unidirectional (TX) and bidirectional .
Testing	Testing progress bar. Click Start to displays the testing progress.

Survey

Index	BSSID	SSID	MAXtream	Device Name	SNR(dB)	Signal / Noise(dBm)	Channel	Security
1	50-C7-BF-04-BF-26	TP-LINK_BF28_5G	No		38	-63/-101	5805 (161)	WPA2-PSK
2	60-E3-27-D0-E2-2A	jjjj5	No		34	-61/-95	5220 (44)	WPA2-PSK
3	50-C7-BF-08-5D-86	TP-LINK_Cui5	No		38	-57/-95	5220 (44)	WPA2-PSK
4	18-A6-F7-F3-47-1A	TP-LINK_Cui5re	No		41	-54/-95	5220 (44)	WPA-PSK/WPA2-PSK
5	18-A6-F7-20-02-E1	EAP225 5g	No		38	-61/-99	5765 (153)	WPA2-PSK
6	18-A6-F7-F3-71-BA	hubiao2.5	No		33	-62/-95	5180 (36)	WPA-PSK/WPA2-PSK
7	EC-08-6B-00-F4-3A	TP-LINK_F43A	No		20	-75/-95	5180 (36)	WPA-PSK/WPA2-PSK
8	50-C7-BF-01-88-1F	7200_5G	No		45	-50/-95	5180 (36)	WPA-PSK/WPA2-PSK
9	C4-E9-84-ED-08-C3	ap3200_5G_1	No		28	-67/-95	5180 (36)	WPA2-PSK
10	18-A6-F7-2D-CA-77	EAP_TEST	No		35	-60/-95	5180 (36)	WPA2-PSK
11	50-C7-BF-01-0B-FA	C9test-5	No		34	-61/-95	5180 (36)	WPA-PSK/WPA2-PSK
12	50-C7-BF-06-A8-BD	TP-LINK_A8BE_5G	No		38	-57/-95	5200 (40)	WPA-PSK/WPA2-PSK
13	18-A6-F7-F3-4D-42	jjjj5re	No		36	-59/-95	5220 (44)	WPA-PSK/WPA2-PSK
14	F4-F2-6D-EF-69-53	ARC2_5G	No		30	-65/-95	5220 (44)	WPA2-PSK
15	50-C7-BF-0B-BE-01	eap_fuck000_5G	No		29	-66/-95	5240 (48)	WPA2-PSK
16	F4-F2-6D-D2-8F-7D	TP-LINK_8F7C_5G	No		29	-66/-95	5240 (48)	WPA-PSK/WPA2-PSK
17	F4-F2-6D-B6-AC-5D	TP-LINK_AC5E_5G	No		45	-53/-98	5745 (149)	WPA-PSK/WPA2-PSK
18	D0-EE-07-1C-89-54	autoss	No		7	-91/-98	5745 (149)	WPA-PSK/WPA2-PSK
19	00-0A-EB-13-7A-FE	TP-LINK_7AFE_5G	No		44	-42/-86	5765 (153)	WPA-PSK/WPA2-PSK
20	90-F6-52-C3-B0-B8	TestingRoom	No		32	-67/-99	5765 (153)	WPA-PSK/WPA2-PSK
21	EC-08-6B-9F-BD-2A	Smart Home5G	No		47	-52/-99	5765 (153)	WPA-PSK/WPA2-PSK
22	F6-F2-6D-2F-A3-24	onhub	No		42	-57/-99	5765 (153)	WPA2-PSK

AP Count: 26 Refresh

BSSID Displays the BSSID of other APs surveyed by this device.

SSID Displays the SSID of other APs surveyed by this device.

MAXtream Displays the MAXtream capability of other APs surveyed by this device.

Device Name Displays the names of other APs surveyed by this device.

SNR (dB) Displays the Signal Noise Ratio (Unit: dB) of other APs surveyed by this device.

Signal/Noise (dBm) Displays the signal and noise value (Unit: dBm) of other APs surveyed by this device.

Channel Displays the channels of other APs surveyed by this device.

Security Displays the security mode of other APs surveyed by this device.


AP Count Displays the number of other APs surveyed by this device.

Refresh Refresh this page by clicking **Refresh**.


Spectrum Analysis

Spectrum Analysis can help you to choose the proper channel/frequency. Through the spectrum analysis you can learn the distribution of the radio noise and intelligently select the channel/frequency in low noise.

1. Click **Spectrum Analysis** in the tools' drop-down list, the following window will pop up to remind you that all wireless connections will be lost during spectrum analysis. Click **Yes** and you will then get into Spectrum Analysis page.



2. Click **Start**, the PharOS will begin to analyze the power of frequency. Observe the curves for a period of time, and then click **stop**. Note that the relatively low and continuous part of the average curve indicates less radio noise. Here we take the figure below as an example.




NOTE:

Only CPE610/CPE510/CPE520/WBS510 has the select box of **Frequency Range** at the top-left corner. Select the required range and then click **Start**.

3. When choosing channel/frequency, we should try to avoid the spectrum with large radio noise. In this example, the recommended channel/frequency is 1/2412MHz.

Appendix A: Pharos MAXstream TDMA

With the fast expansion of network scale, wireless competition and collisions among CPEs and base stations will be so enormous that the real throughput of the network will drop, resulting in a serious impact on end-user experience. To mitigate these effects, TP-Link's Pharos series develops MAXstream TDMA Technology.




Pharos MAXstream is a proprietary protocol developed on the basis of TDMA (Time Division Multiple Access) by TP-Link. MAXstream cuts each wireless data frame transmission into certain number of time slots according to the client connections priority, greatly boosting efficiency of the wireless channel.

The MAXstream technology has the following advantages which make it ideal for point to multi-point links:

- Eliminates hidden node collisions and improves channel efficiency
- Lower latency, higher throughput, larger network capacity and more stability

To enable the MAXstream function among the AP and stations, you only need to select **MAXstream** option on the **Wireless** tab of the Pharos web management page of the AP, as shown in the following figure. Stations will automatically adjust their connections according to AP's MAXstream capability.



NOTE:

Pharos MAXstream is a non-standard Wi-Fi protocol that is only compatible with TP-Link's Pharos series products. Please notice that you will not be able to connect other Wi-Fi devices to an AP with MAXstream enabled.

Appendix B: Glossary

	Glossary	Description
A	ALG (Application Layer Gateway)	Application Level Gateway (ALG) is application specific translation agent that allows an application on a host in one address realm to connect to its counterpart running on a host in different realm transparently.
	ARP (Address Resolution Protocol)	Internet protocol used to map an IP address to a MAC address.
C	CPE (Customer Premise Equipment)	A terminal located at a subscriber's premises and connected with a carrier's telecommunication channel at the demarcation point. The point is established in a building or complex to separate customer equipment from the equipment located in either the distribution infrastructure or central office of the Communications Service Provider.
D	DDNS (Dynamic Domain Name Server)	The capability of assigning a fixed host and domain name to a dynamic Internet IP address.
	DFS (Dynamic Frequency Selection)	A method applied in wireless networks, which is used for radar avoidance and is supported by the novel IEEE 802.11h wireless local area network standard.
	DHCP (Dynamic Host Configuration Protocol)	A protocol that automatically configures the TCP/IP parameters for all the PCs that are connected to a DHCP server.
	DMZ (Demilitarized Zone)	A Demilitarized Zone allows one local host to be exposed to the Internet for a special-purpose service such as Internet gaming or videoconferencing.
	DNS (Domain Name Server)	An Internet Server that translates the names of websites into IP addresses.
	DoS (Denial of Service)	A hacker attack designed to prevent your computer or network from operating or communicating.
F	FTP (File Transfer Protocol)	Application protocol, part of the TCP/IP protocol stack, used for transferring files between network nodes.
H	HTTP (Hypertext Transfer Protocol)	The protocol used by Web browsers and Web servers to transfer files, such as text and graphic files.

	Glossary	Description
I	ICMP (Internet Control Messages Protocol)	Network layer Internet protocol that reports errors and provides other information relevant to IP packet processing.
	Internet	Largest global Internetwork, connecting tens of thousands of networks worldwide and having a "culture" that focuses on research and standardization based on real-life use.
	IP (Internet Protocol)	Network layer protocol in the TCP/IP stack offering a connectionless Internetwork service. IP provides features for addressing, type-of-service specification, fragmentation and reassembly, and security.
	ISP (Internet Service Provider)	Company that provides Internet access to other companies and individuals.
	IPsec (IP Security)	A framework of open standards that provides data confidentiality, data integrity, and data authentication between participating peers.
L	LAN (Local Area Network)	High-speed, low-error data network covering a relatively small geographic area (up to a few thousand meters). LANs connect workstations, peripherals, terminals, and other devices in a single building or other geographically limited area.
M	MAC address (Media Access Control address)	Standardized data link layer address that is required for every port or device that connects to a LAN. Other devices in the network use these addresses to locate specific ports in the network and to create and update routing tables and data structures. MAC addresses are 6 bytes long and are controlled by the IEEE.
	MTU (Maximum Transmission Unit)	The size in bytes of the largest packet that can be transmitted.
N	NAT (Network Address Translator)	Mechanism for reducing the need for globally unique IP addresses. NAT allows an organization with addresses that are not globally unique to connect to the Internet by translating those addresses into globally routable address space.
	NTP Server	NTP Server is used for synchronizing the time across computer networks.
P	PPPoE (Point-to-Point Protocol over Ethernet)	PPPoE is a network protocol for encapsulating Point-to-Point Protocol (PPP) frames inside Ethernet frames.

	Glossary	Description
S	SMTP (Simple Mail Transfer Protocol)	SMTP is an Internet standard for electronic mail (e-mail) transmission
	SSH (Secure Shell Protocol)	SSH is a network protocol that allows data to be exchanged using a secure channel between two networked devices.
	SSID	A Service Set Identification is a thirty-two character (maximum) alphanumeric key identifying a wireless local area network. For the wireless devices in a network to communicate with each other, all devices must be configured with the same SSID. This is typically the configuration parameter for a wireless PC card. It corresponds to the ESSID in the wireless Access Point and to the wireless network name.
	SNMP (Simple Network Management Protocol)	SNMP provides a management frame to monitor and maintain the network devices. With SNMP function enabled, network administrators can easily monitor the network performance, detect the malfunctions and configure the network devices.
T	TCP (Transfer Control Protocol)	Connection-oriented transport layer protocol that provides reliable full-duplex data transmission.
	TCP/IP (Transmission Control Protocol/ Internet Protocol)	Common name for the suite of protocols to support the construction of worldwide Internet works. TCP and IP are the two best-known protocols in the suite.
	TDMA (Time Division Multiple Access)	TDMA (Time Division Multiple Access) cuts each wireless data frame into certain number of time slots according to the client connections priority, greatly boosting efficiency of the wireless channel.
U	UDP (User Datagram Protocol)	UDP is a simple protocol that exchanges datagram without acknowledgments or guaranteed delivery, requiring that error processing and retransmission be handled by other protocols.
	UPnP (Universal Plug and Play)	UPnP is a set of networking protocols for primarily residential networks without enterprise class devices that permits networked devices.
V	VLAN (Virtual Local Area Network)	Group of devices on one or more LANs that are configured (using management software) so that they can communicate as if they were attached to the same wire, when in fact they are located on a number of different LAN segments. Because VLANs are based on logical instead of physical connections, they are extremely flexible.
	VPN (Virtual Private Network)	Enables IP traffic to travel securely over a public TCP/IP network by encrypting all traffic from one network to another.

	Glossary	Description
W	WAN (Wide Area Network)	Data communications network that serves users across a broad geographic area and often uses transmission devices provided by common carriers.
	WEP (Wired Equivalent Privacy)	A data privacy mechanism based on a 64-bit or 128-bit or 152-bit shared key algorithm, as described in the IEEE 802.11 standard.
	Wi-Fi	A trademark of the Wi-Fi Alliance, founded in 1999 as Wireless Internet Compatibility Alliance (WICA), comprising more than 300 companies, whose products are certified by the Wi-Fi Alliance, based on the IEEE 802.11 standards (also called Wireless LAN (WLAN) and Wi-Fi). This certification warrants interoperability between different wireless devices.
	WISP (Wireless Internet Service Provider)	WISPs are Internet service providers with networks built around wireless networking. The technology used ranges from commonplace Wi-Fi mesh networking or proprietary equipment designed to operate over open 900MHz, 2.4GHz, 4.9, 5.2, 5.4, and 5.8GHz bands or licensed frequencies in the UHF or MMDS bands.
	WLAN (Wireless Local Area Network)	A group of computers and associated devices communicate with each other wirelessly, which network serving users are limited in a local area.