URINALS

Siphonic urinal CASA 84014.1



| TECHNICAL DATA | |
|---------------------|---|
| Order no. | 84014.1 |
| Certified to | DIN 1390 |
| matching for | LIS CU2 Concealed frame for urinal without |
| | integrated control, order no. 89266.4 |
| | LIS SMART CONTROL-U, order no. 37066.0 |
| Specification | Only to be used with cover |
| Water inlet | concealed |
| Outlet | horizontal |
| Flushing quantity | minimum 2 I |
| Flushing capacity | minimum 0.3 l/s |
| Weight | 10,0 kg |
| Accessories excl. | Cover for urinal, order no. 89414.1 |
| Mounting acc. incl. | Fixing srews, order no. 89553.8 |
| Mounting acc. excl. | LIS CU2 horizontal inlet connection, |
| | order no. 89900.7 |
| | LIS SMART CONTROL-U horizontal inlet |
| | connection, order no. 89418.9 |
| | Siphon with concealed outlet, order no. 89415.3 |

| Colours | see colour table | |
|---|------------------|--|
| SPECIFICATION TEXT | | |
| Siphonic urinal Laufen-CASA, sanitary ceramic | | |
| DIN 1390, dimensions 305 x 285 x 465 mm | | |
| only to be used with cover | | |
| minimum 2-I flush, water inlet concealed, outlet horizontal, | | |
| flushing rate minimum 0.3 l/s | | |
| Special feature: Vacuum and performance tested | | |
| Further options / accessories: LIS horizontal inlet connection, siphon with | | |
| concealed outlet, urinal cover, LIS CU2 concealed frame for urinal with- | | |
| out integrated control or LIS SMART CONTROL-U concealed kit for | | |
| urinal flash control and front plate with infrared sensor | | |
| Order no. 84014.1 | | |

TECHNICAL DRAWINGS / S 1 : 20







