

★ SEMI-SYNTHETIC GEAR OIL.

This gear oil is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality special refined and synthetic base oils and special EP-additives to obtain the following properties:

- excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- fuel economy

★ APPLICATIONS

This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

★ PERFORMANCE LEVEL

- API: GL-5
- MT-1
- SCANIA: STO 1.0
- SAE: J2360
- ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
- MB 235.8
- MACK GO-J
- MAN 34122, 341 E3, 342 M3
- IVECO AXLES
- VOITH 3.325-340
- MIL-L-2105E
- ARVIN MARITOR O-76N
- TMS-6816

★ CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.882
Viscosity 40 °C	mm ² /s		87.90
Viscosity 100 °C	mm ² /s		15.20
Viscosity Index			184
Flash Point COC	°C		200
Pour Point	°C		-42



★ PACKAGING



12x1L

4x4L

3x5L

20L

60L

210L

IBC