

BMD51316



BMD51316 Switch Disconnecter 3P, 16A



General Information

| | |
|-----------------------|--|
| Extended Product Type | BMD51316 |
| Product ID | 2CDD643051R0016 |
| EAN | 4016779038423 |
| Catalog Description | BMD51316 Switch Disconnecter 3P, 16A |
| Long Description | The basic M switch disconnecter is suitable for commanding loads according to IEC 60947-3. |

Ordering

| | |
|------------------------|---------------|
| EAN | 4016779038423 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85369095 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 52.5 mm |
| Product Net Height | 69 mm |
| Product Net Depth / Length | 88 mm |
| Product Net Weight | 0.21 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 4 piece |
| Package Level 1 Width | 92 mm |
| Package Level 1 Height | 80 mm |
| Package Level 1 Depth / Length | 220 mm |
| Package Level 1 Gross Weight | 0.901 kg |
| Package Level 1 EAN | 4016779038430 |
| Package Level 2 Units | 32 piece |
| Package Level 2 Width | 183 mm |
| Package Level 2 Height | 164 mm |
| Package Level 2 Depth / Length | 445 mm |
| Package Level 2 Gross Weight | 7.208 kg |
| Package Level 2 EAN | 4016779051965 |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
|-------------------------|--|

Additional Information

| | |
|---------------------------------|---|
| Actuator Type | Toggle |
| Connecting Capacity | Flexible 25 mm ² Rigid 35 mm ² |
| Degree of Protection | IP20 |
| Number of Poles | 3 |
| Number of Protected Poles | 3 |
| Product Main Type | Basic M BMD |
| Product Name | Switch Disconnecter |
| Rated Current (I _n) | 16 A |
| Rated Frequency (f) | 50 Hz 60 Hz |
| Rated Operational Voltage | 415 V AC |
| Recommended Screw Driver | Pozidriv 2 |
| Remarks | IP40 in enclosure with cover |
| RoHS Date | 20170816 |
| Standards | IEC 60947-3 |
| Terminal Type | Screw Terminals |
| Tightening Torque | 2 N·m |
| Wire Stripping Length | 12.5 mm |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|---------------------|
| Data Sheet, Technical Information | 9AKK107045A1496 |
| Declaration of Conformity - CE | 2CDK400668D2701 |
| Instructions and Manuals | on the product body |
| RoHS Information | 2CDK400669D0201 |

Classifications

| | |
|---------------|--|
| ETIM 5 | EC001545 - Main switch for distribution board |
| ETIM 6 | EC001545 - Main switch for distribution board |
| ETIM 7 | EC001545 - Main switch for distribution board |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | 7.0 27142301 |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Basic M System → Switch Disconnectors

