

BMR415C20



BMR415C20 RCBO, 1P+N, AC, C-Char., 4.5kA, 20A, 0.03A



General Information

Extended Product Type	BMR415C20
Product ID	2CSR645041R1204
EAN	8012542191834
Catalog Description	BMR415C20 RCBO, 1P+N, AC, C-Char., 4.5kA, 20A, 0.03A
Long Description	<p>The basic M RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents.</p> <p>Protection against fault current to earth.</p> <p>Protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).</p> <p>This product is manufactured according to international IEC standards.</p>

Ordering

EAN	8012542191834
Minimum Order Quantity	1 piece
Customs Tariff Number	85363030

Dimensions

Product Net Width	0.035 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.190 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.047 m
Package Level 1 Height	0.078 m
Package Level 1 Depth / Length	0.103 m
Package Level 1 Gross Weight	0.210 kg
Package Level 1 EAN	8012542191834
Package Level 2 Units	5 piece
Package Level 2 Width	0.253 m
Package Level 2 Height	0.088 m
Package Level 2 Depth / Length	0.108 m
Package Level 2 Gross Weight	1.050 kg

Package Level 2 EAN

8012542191841

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
-------------------------	--

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 A
-------------------------------------	--------

Additional Information

Actuator Type	Toggle
Ambient Temperature	-25...55 °C
Connecting Capacity	Flexible 16 mm ² Rigid 25 mm ²
Degree of Protection	IP40
Energy Limiting Class	3
Number of Poles	2
Number of Protected Poles	1
Overvoltage Category	III
Pollution Degree	2
Product Main Type	Basic M BMR
Product Name	Residual Current Circuit Breaker with Overcurrent Protection
Rated Current (I_n)	20 A
Rated Frequency (f)	50 Hz
Rated Residual Current	30 mA
Rated Voltage (U_r)	230 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Rated Insulation Voltage (U_i)	500 V
Rated Operational Voltage	230 V AC
Rated Short-Circuit Capacity (I_{cn})	4.5 kA
Recommended Screw Driver	Pozidriv 2
Release Type	C
Standards	IEC 61009-1
Tightening Torque	2 N·m
Tripping Characteristic	C
Type of Residual Current	AC Type
Wire Stripping Length	12.5 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107045A1496
Declaration of Conformity - CE	2CSC422004D2701
Instructions and Manuals	on the product body

Classifications

ETIM 6	EC000905 - Earth leakage circuit breaker
ETIM 7	EC000905 - Earth leakage circuit breaker
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Basic M System → Residual Current Devices RCDs

