



### Typical Inspection Data:

<b>Colour</b>	Copper
<b>Copper Content</b>	8.5 %wt
<b>Texture</b>	Smooth
<b>Thickener</b>	Bentonite
<b>Unworked Penetration @ 25 °C</b>	285 mm <sup>10</sup> <sup>-1</sup>
<b>Operating Temperature Range</b>	-40 °C to 1150 °C
<b>Drop Point</b>	Infusible

## Copper Ease

### Product Features:

- Anti-seize assembly compound with extreme temperature tolerance (-40 °C to +1150 °C).
- Forms a dense protective coating over metal parts - will not wash or burn off.
- Helps prevent brake disc squeal when applied to the back of brake pads.
- Improves sealing and eases assembly and dismantling of:
  - Cylinder head gaskets and bolts
  - Gaskets of all descriptions
  - Steering and suspension
  - Universal joints
  - Spark plugs
  - Nuts and bolts
  - Exhaust systems
- Suitable for automatic and individual applications

### Directions for use:

1. Clean all surfaces before application.
2. To prevent disc squeal: apply directly to callipers and back of disc pad.
3. Warning: Do not apply to friction material or disc.

### Handling:

- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.

16-02-2017