OEM SPECIFIC ATF MB

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

APPLICATIONS

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics, it is not suitable for other applications.

FEATURES

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MB

236.14

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm²/s	28.6
Kinematic viscosity at 100°C	ASTM D445	mm²/s	5.9
Viscosity index	ASTM D2270		154
Pour point Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11800
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL	·	RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION°