

Gauge	1/10	
Manufacturing	Level loop	
Pile description	PP Tristar	
Primary backing	Woven	
Pile weight	300 gr/m ²	
Number of tufts	155.511 /m ²	
Secondary backing	Easyback	
Width	400 cm	500 cm
Total weight	1170 gr/m ²	1170 gr/m ²
Total height	5 mm	5 mm
Pile In/Out	Out	Out
Roll length	40 m	40 m
DOP	1087#00091/00091/3	
Fire classification	Efl	
Use classification	22	
TOG rating	1	

Available colours Easyback | 400/500 cm 004 | 010 | 019 | 027 | 028 | 029 | 031 | 037 | 110 | 116 | 141 | 153 | 446 | 897 | 990 |

Colour legend	004	Honey	010	Gold	019	Charcoal
	027	Teak	028	Ocean	029	Mouse
	031	Tomato	037	Beaver	110	Moonlit
	116	Stone	141	Black	153	Dark Grey
	446	Port	897	Midnight Blue	990	Fondant



These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

BIG Floorcoverings nv Rijksweg 442 | 8710 Wielsbeke - Belgium | T +32 (0)56 67 42 11 | F +32 (0)56 67 48 40 | www.ideal-bintg.com

16.10.2018 | ISO N090N02/2/01-01-10



Beaulieu
International
Group



004 - 400/500 cm



010 - 400/500 cm



019 - 400/500 cm



027 - 400/500 cm



028 - 400/500 cm



029 - 400/500 cm



031 - 400/500 cm



037 - 400/500 cm



110 - 400/500 cm



116 - 400/500 cm



141 - 400/500 cm



153 - 400/500 cm



446 - 400/500 cm



897 - 400/500 cm



990 - 400/500 cm