



## TransFlow ML 10W-30 Semi Synthetic

### Recommended by Comma for applications requiring:

Ford M2C159B, Ford M2C159C, FNH 82009201 (10W-30), FNH 82009202 (15W-30), MF M1145, MF M1144, JD J27, Ford M2C86C, Ford M2C134(A,C,D), HN420A MF M1135, MF1143, CAT TO-2, API GL-4, Allison C-4, FNHA-2-C-201.00; ACEA E3; API CG-4, CF-4, CF, CE/SF, CD/SF, CD/SE; Sperry Vickers / Eaton M2950S, Sperry Vickers / Eaton: I-280-S, Sauer Sunstrand / Danfoss Hydrostatic Trans Fluid, MF M1139, JD J20C, CNH Mat 3525, M1127A, HN420A, NH410B; ZF TE-ML 05K, 07D, 06B, 06C, 07B

### Typical Inspection Data:

Density @ 20°C	0.869 g/cm <sup>3</sup>
Viscosity @ 100°C	9.8 cSt
Viscosity @ 40°C	65 cSt
Viscosity Index	135
Viscosity CCS @ -25°C	5900 cP
T.B.N.	10.7 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.15%
Calcium	0.35%
Phosphorus	0.15%
Colour	Brown
Flash Point	200°C
Pour Point	-36°C

### Product Features:

- Suitable for most agricultural and construction equipment requiring a multipurpose STOU type product.

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 17-01-19