



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Ultrance VCC 0W-20

Fully synthetic mid SAPS motor oil for gasoline and diesel engines

Description:

Eurol Ultrance VCC 0W-20 is a fully synthetic fuel economy oil for gasoline and diesel engines in passenger cars, especially for the most recent Volvo engines. Eurol Ultrance VCC 0W-20 is intended for the new Volvo Engine Architecture (VEA engines) technology.

VCC RBS0-2AE specification, Eurol Ultrance VCC 0W-20 has a HTHS below 2.9 cP.

Eurol Ultrance VCC 0W-20 provides an extremely quick and stable lubricant film at the cold start at low temperatures and offers high thermal stability under heavy duty operating conditions.

Eurol Ultrance VCC 0W-20 offers optimum dispersancy and detergency by keeping the engine clean. Provides maximum protection against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Ultrance VCC 0W-20 offers extra fuel saving properties and allows long drain intervals (up to 30.000 km) for the latest models of Volvo. In order to achieve the requested fuel economy performance of the Volvo

Specifications

Approved

API SN

Volvo VCC RBS0-2AE

Performance level

ACEA C5

Physical properties

Colour	Yellow	
Density at 20°C	0.842 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	47.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9 cSt	ASTM D 445
Viscosity Index	175	ASTM D 2270
Viscosity, dynamic (CCS)	5687 cP	ASTM D 2602
Base number	7.9 mg KOH/g	ASTM D 2896
Sulphated ash	0.8 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

E100017

Version 8.0, 06-04-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com