



ALU-FREEZE G12+

A "longlife" OAT (Organic Additives Technology) anti-freeze based on monoethyleneglycol and selected additives to obtain the following properties:

- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behaviour towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free



Приложения

May be used all the year round in cooling systems of gasoline and diesel engines. This anti-freeze should be diluted with demineralized water before use, in accordance with the ratio in the owner's manual or given below. Specially suitable for use according to the specifications mentioned below.

Показатели деятельности

- | ASTMD D3306
- | ASTM D 4985
- | SAE J 1034
- | BS 6580 (2010)
- | AFNOR NF R15-601
- | FFV HEFT R 443
- | CUNA NC 956-16
- | UNE 26361-88
- | JIS K 2234
- | NATO S 759
- | CHRYSLER MS 9176
- | CUMMINS CES 14603
- | FORD ESE M97B49-A WSS-M97B44-D ESD M97 B49-A
- | GM1899 M US 6277 M OPEL GM QL130100
- | JOHN DEERE H 24 B1 & C1
- | LEYLAND TRUCKS LTS 22 AF10
- | MACK 014GS 17004
- | MAN 248 324 (SNF) & B&W D 36 5600
- | MERCEDES MB 325.3
- | RENAULT 41-01-001-D
- | VAG TL 774 D/F
- | VOLVO VCS

Характеристики

	Unit	Average Value
Цвет		RED
Плотность при 15 °C	kg/l	1.124

Упаковка

