







ENERGY-SAVING TOWER UPS



The energy-saving UPS to save up to 93% of power consumption

Designed for home, SOHO office and office applications, the UT Series adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The patented GreenPower UPS™ Bypass design achieves ultra-low power consumption to reduce energy costs. The LED indicator shows the utility, battery and operating status of the UPS. Other features include overload protection, EMI filter and configurable alarm to safeguard your devices.

APPLICATION




- Home
- Office
- SOHO Office

SERIES FEATURES

- Line-interactive UPS Topology
- Automatic Voltage Regulation (AVR)
- LED Status Indicator
- High-Speed Ethernet Data Transmission
- Configurable Alarm
- Energy Saving Technology
- Generator Compatible
- Phone/Fax/Modem/DSL/Network Protection
- EMI and RFI Filtration
- PowerPanel® Management Software

PRODUCT CALLOUTS

1. Power On/Off Switch
2. LED Status Indicators
3. USB Port
4. Battery Backup Outlets
5. Input Circuit Breaker
6. Communication Protection Ports RJ11/RJ45
7. AC Input Power Cord





TECHNICAL SPECIFICATIONS

Model Name	UT1100EG	UT1100EIG
General		
UPS Topology	Line-interactive	Line-interactive
Energy Saving Technology	GreenPower UPS™ Bypass Technology	GreenPower UPS™ Bypass Technology
Input		
Generator Compatibility	Yes	Yes
Nominal Input Voltage (Vac)	230 ± 10%	230 ± 10%
Input Voltage Range (Vac)	165 - 290	165 - 290
Input Frequency (Hz)	50 ± 5, 60 ± 5	50 ± 5, 60 ± 5
Input Frequency Detection	Auto-sensing	Auto-sensing
Rated Input Current (A)	4.56	4.56
Input Connector Type	Schuko	Schuko
Output		
Capacity (VA)	1100	1100
Capacity (Watts)	630	630
On Battery Waveform	Simulated Sine Wave	Simulated Sine Wave
On Battery Voltage(s) (Vac)	230 ± 10%	230 ± 10%
On Battery Frequency (Hz)	50 ± 1%, 60 ± 1%	50 ± 1%, 60 ± 1%
Automatic Voltage Regulation (AVR)	Single Boost, Single Buck	Single Boost, Single Buck
Overload Protection	Circuit Breaker	Circuit Breaker
Outlet(s) - Total	4	6
Outlet Type	Schuko x 4	IEC C13 x 6
Outlet(s) - Battery Backup	4	6
Typical Transfer Time (ms)	4	4
Battery		
Runtime at 60W (min)	65	65
Runtime at 90W (min)	43	43
Runtime at 200W (min)	14	14
Typical Recharge Time (Hours)	6	6
User-replaceable	No	No
Battery Type	Sealed Lead-acid	Sealed Lead-acid
Surge Protection & Filtering		
EMI/RFI Filtration	Yes	Yes
Phone/Network Protection RJ11/RJ45 (Combo)	1-in, 1-out	1-in, 1-out
Management & Communications		
LED Indicators	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault	Power On, Line Mode, Battery Mode, Bypass Mode, Low Battery, Overload, UPS Fault
HID Compliant USB Port(s)	1	1
Audible Alarms	Battery Mode, Low Battery, Overload, UPS Fault	Battery Mode, Low Battery, Overload, UPS Fault
Ethernet Data Transmission Speed	Up to 1Gb	Up to 1Gb
Power Management Software	PowerPanel® Personal Edition	PowerPanel® Personal Edition
Physical		
Form Factor	Tower	Tower
Physical Size - UPS Module		
Dimensions (WxHxD) (mm.)	95 x 220 x 307	94 x 220 x 307
Weight (kg.)	6.9	6.9
Environmental		
Operating Temperature (°C)	0 - 40	0 - 40
Operating Relative Humidity (Non-condensing) (%)	0 - 90	0 - 90
Online Thermal Dissipation (BTU/hr)	8	8
Certifications		
Certifications*	CE, EAC	CE, EAC
RoHS	Yes	Yes

*Certifications may vary according to different regions. Visit www.cyberpower.com for more information.
 #All specifications are subject to change without notice.