



GDO1N+GBN

Single opening shower door GDO1N in a combination with a solid sidewall GBN

The latest frameless ELEGANT NEO range is remarkable with its **lightweight** and pure design, allowing the airiness and elegance of each product to stand out. But it is really unique because of its unmatched range of installation dimensions, so you won't have to limit yourself. It uses 6 mm safety glass with ROLSHIELD protective coating applied, high-quality chrome steel fittings and integrated strut. With a standard height of 2000 mm, it provides all the necessary solutions for your bathroom.







Туре	Order number	Profile	Height (h)	Installation width (y)	Glass	Delivery	Side part width (s)	Entrance size (c)
GDO1N/800	188-8000000-00-02	Brillant	2015 mm	685-785	Transparent	S	290	380-480
GDO1N/900	188-9000000-00-02	Brillant	2015 mm	785-885	Transparent	S	290	480-580
GDO1N/1000	188-1000000-00-02	Brillant	2015 mm	885-985	Transparent	S	290	580-680
GDO1N/1100	188-1100000-00-02	Brillant	2015 mm	985-1085	Transparent	S	290	680-780
GDO1N/1200	188-1200000-00-02	Brillant	2015 mm		Transparent	S	290	780-880
GBN/800	189-8000000-00-02	Brillant	2005 mm		Transparent	S		



Туре	Order number	Profile	Height (h)	Installation width (y)	Glass	Delivery	Side part width (s)	Entrance size (c)
GBN/900	189-9000000-00-02	Brillant	2005 mm		Transparent	S		
GBN/1000	189-1000000-00-02	Brillant	2005 mm	985-995	Transparent	S		

^{*} H - height including supporting elements

DELIVERY METHOD:

- **S** items in **S**TOCK delivery in the earliest possible date
- O items to ORDER delivery time should not exceed 14 working days
- **Z** CUSTOMI**Z**ED items delivery time should not exceed 30 working days

ATTENTION: Nominal sizes of shower enclosures are designed for INSTALLATION ON THE TRAY and they are always assembled with indentation from the edge of the tray. With INSTALLATION ON THE TILES there is a risk, that the size of shower enclosure will be smaller than measured width of the tiles. It is necessary to follow the size charts specified in "TECHNICAL SPECIFICATION" file, which is available to download on the product pages.