

More compact, lighter, cleaner and more efficient

For total elimination of air from heating and cooling installations. Air separators increase comfort and improve the yield. Air separators also offer benefits in the event of application in old systems or when an open system is converted to a closed system.

- Increases comfort and yield.
- The removal of air from the system water extends the service life of pumps, control equipment and other system accessories.



The Flamcovent Smart air separators remove even the smallest microbubbles from the system water. They are virtually maintenance-free and the flow resistance is negligibly low.

Advantages


- 60% better performance compared to conventional separators.
- Flow velocity up to 3 m/s.
- Can be used with all kinds of pipework.
- Compact dimensions, light weight.
- Extremely low flow resistance and low loss of energy.
- Consistent performance throughout its service life.

Technical Specifications



- Minimum/Maximum working temperature: -10 °C / 120 °C.
- Maximum working pressure: 10 bar.
- Suitable for addition of glycol-based anti-freeze up to 50%.




| | | |
|----------------|-------------------------|-----|
| Description | Flamcovent Smart G1½"F | |
| Order Code | 30005 | |
| GTIN | 08712874300057 | |
| Model | <u>Flamcovent Smart</u> | |
| Connection (E) | G 1 ½" F | |
| Dimensions | A [mm] | 94 |
| | C [mm] | 193 |
| | D [mm] | 129 |
| | K [mm] | 109 |
| | L [mm] | 173 |
| | M [mm] | 54 |
| | H/H1 [mm] | 238 |
| | H2 [mm] | 227 |
| Ø N [mm] | 92 | |
| Weight [kg] | 1.73 | |



Selection table for Flamcovent & Clean Smart series



Selection table for Flamcovent & Clean Smart series



Classification General Data

| | |
|----------------------|--------------------------------------------------------|
| Etim Group | Filters/separators |
| Etim Class | Air-/dirt separator for central heating/cooling system |
| Product Name | Flamcovent Smart G1½"F |
| Brand | Flamco |
| Product Type | 1 1/2 |
| Artikelnummer | 30005 |

Attributes

| | |
|----------------------------------------------|------------------------------------------------|
| Material | Plastic |
| Housing material | Other |
| Housing material quality | Other |
| Separator type | Air |
| Model | Horizontal/vertical |
| Suitable for heating | Yes |
| Suitable for cooling | Yes |
| Nominal diameter | 1 1/2 inch (40) |
| Outer pipe diameter | 48.3 Millimetre |
| Connection | Internal thread cylindrical BSPP-G (ISO 228-1) |
| Construction length | 129 Millimetre |
| Article compression class | PN 10 |
| Surface protection | Untreated |
| Operating principle | Other |
| Flow-through capacity | 0 - 15.48 m ³ /h |
| Suitable for open system | No |
| With blow-off valve | Yes |
| Suitable for closed system | Yes |
| With drain valve | No |
| With dismountable filter | No |
| Backwash filter | No |
| With automatic de-aerator | Yes |
| Max. medium temperature (continuous) | 120 Degrees celsius |
| With integrated replenishment automat | No |
| With couplers | No |
| Inlet/outlet offset distance | 0 Millimetre |
| Max. operating pressure | 10 Bar |
| Variable flow direction | No |
| With insulation | No |

Find more information online:

[Installation and operating instruction](#)

[Declaration of Conformity](#)

[Flamcovent Smart ADSK](#)

[Flamcovent Smart ADSK Revit](#)

[Flamcovent Smart DWG](#)

[Flamcovent Smart STEP](#)

[Export catalogue](#)

[Brochure](#)

[Specification Text](#)

[Packaging data](#)

[Flamcovent & Clean Smart](#)



Flamco

Flow of Innovation

30005 - Flamcovent Smart 1 1/2

Product Data Sheet 2022/08/11

[Installation and operating instruction](#)

[Declaration of Conformity](#)

[Flamcovent Smart ADSK](#)

[Flamcovent Smart ADSK Revit](#)

[Flamcovent Smart DWG](#)

[Flamcovent Smart STEP](#)

[Export catalogue](#)

[Brochure](#)

[Specification Text](#)

[Packaging data](#)

[Flamcovent & Clean Smart](#)

Fort Blauwkapel 1

1358 DB, Almere - nl

T +31 (0)36 52 62 300

E info@aalberts-hfc.com

I flamcogroup.com