



unbalanced pro audio / instrument cable coaxial - conductive layer - PVC

- 0.22 mm² conductor cross section (AWG 24)
- double shielding
- conductive plastic layer
- bare copper spiral shield
- capacitance: 115 pF/m (35 pF/ft)

PVC

This robust, well shielded audio cable offers especially good handling due to its low external diameter. It is suited for high-impedance instruments as well as for wiring of Pedal boards and Line level devices.

construction

cond. construction	stranded bare copper, 7 x 0.20 mm
cond. cross section	0.22 mm ²
insulation	polyethylene (PE)
1. shield	conductive plastic layer
2. shield	bare copper spiral shield
outer jacket	PVC, matt
overall diameter	6.1 mm

mechanics

min. bending radius	30 mm
working temperature	-20°C / +70°C

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./shield	115 pF/m
insulation resistance	> 1 GΩ x km

order code	cable color	weight kg/m	standard lengths m
AC104SW	black	0.04	30 / 50 / 100 / 200 / 300 / 500
AC104BL	blue	0.04	30 / 50 / 100 / 200 / 300 / 500
AC104RT	red	0.04	30 / 50 / 100 / 200 / 300 / 500

technical specifications are subject to change