



MANNOL ATF AG55



GB

Mannol ATF AG55 is a multifunctional ATF for use in modern 6-speed automatic transmission in cars and commercial vehicles. Meets the requirements of the most common specifications of European car manufacturers. Provides an excellent low-temperature switching behavior, stable high friction level and best wear protective properties for reliable operation and long life.

DE

Mannol ATF AG55 ist ein multifunktionales ATF zum Einsatz in modernen 6-Gang-Automatikgetrieben in PKW und Nutzfahrzeugen. Entspricht den Anforderungen der gängigsten Spezifikation Automobil- und Getriebehersteller. Sorgt für ein exzellentes Tieftemperatur-Schaltverhalten, dauerhaft hohes Reibwertniveau und beste Verschleißschutzeigenschaften für zuverlässige Funktion und lange Lebensdauer.

RU

Mannol ATF AG55 специальная высококачественная синтетическая жидкость, предназначенная для современных 6-ступенчатых автоматических коробок передач легковых автомобилей и коммерческой техники. Обеспечивает комфортное переключение передач при низких температурах, защищает от износа пары трения, и способствует продлению срока службы АКПП.

Packages:

1L, 4L, 20L, 60L, 208L, 1000L

Meets the requirements and specifications:

AUDI/VW G 055005 A1/A2/A6

ZF S671 090 252/253/255

BMW 83220142516 (1375.4)/

83220144137

JAGUAR C2C 8432

LAND ROVER TYK500050

HYUNDAI 040000C90SG

MERCON SP

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15°C	D 1298	kg/m ³	840
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-55
Viscosity at 100°C	D 445	CSt	6,07
Viscosity at 40°C	D 445	CSt	28,30
Viscosity index	D 2270		170

Unsere Information stützt sich auf sorgfältige Untersuchungen und darf als zuverlässig gelten, dennoch kann sie nur unverbindlich beraten.

Our information is based on thorough research and may be considered reliable, although not legally binding.

Предоставленная информация основана на данных исследований и является надежной, но не несет юридических обязательств.