



11LMS25
Motor protective
circuit breaker

Product designation

Product type designation

Electrical features

Number of poles	nr.	3
Magnetic protection		Yes
Thermal protection		Yes
Phase failure detection		Yes
Rated insulation voltage U_i	V	690
Rated impulse withstand voltage U_{imp}	kV	6
Rated frequency	Hz	50/60
Thermal trip adjustment range		6,3...10
Rated current (I_n)	A	10
Magnetic tripping		12 x I_n

Operational short-circuit current breaking capacity (I_{cs}) at AC

230V	kA	5
400V	kA	2
500V	kA	2
690V	kA	2

Maximum short-circuit current breaking capacity (I_{cu}) at AC

230V	kA	6
400V	kA	5
500V	kA	2
690V	kA	2

Operations

Mechanical life	Cycles	100,000
Electrical life	Cycles	100,000

Mechanical features

Tightening torque for terminals

min	Nm	2
max	Nm	2
min	lbft	16
max	lbft	16

max number of wires simultaneously connectable

nr. 2

Conductor section

AWG

min	14
max	8

Flexible w/o lug conductor section

min	mm ²	1
max	mm ²	4

Flexible c/w lug conductor section

min	mm ²	1
max	mm ²	4

Flexible with insulated spade lug conductor section

	min	mm ²	1
	max	mm ²	4
Screwdriver			PZ2
Power terminal protection according to IEC/EN 60529			IP20
Cable stripping length	main circuit	mm	1

Ambient conditions

Temperature

Operating temperature

min	°C	-20
max	°C	70

Storage temperature

min	°C	-50
max	°C	80

Compensation temperature

min	°C	-5
max	°C	40

Max altitude		m	3,000
--------------	--	---	-------

Operating position

normal allowable	su piano verticale Qualsiasi
------------------	---------------------------------

Mounting

A vite / profilato
omega 35mm

Weight		g	266
--------	--	---	-----

UL technical data

UL508 / UL60947-4-1 Manual Motor Controller - Short circuit current

Dimensions

Certifications and compliance

Certifications

CSA C22.2 n°14
IEC/EN 60947-1
IEC/EN 60947-2
IEC/EN 60947-4-1
UL508

Compliance

cULus
EAC

ETIM 6 classification