



### Показатели деятельности

- | ACEA: C2
- | PSA: B71 2312
- | FIAT: 9.55535-GS1
- | FIAT: 9.55535-DS1

## SYNTH-MS 0W30

This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines with exhaust after treatment and turbocharger. This specification demands high stability to ensure long oil drain intervals. It also addresses the use of biofuels. There is a fuel economy benefit over a 5W40 reference oil of 4,2%.



### Приложения

This product was primarily developed for mandatory use in the PSA EURO VI Blue HDi DW10F engines and particularly ones equipped with e-HDi using Stop & Start technologies. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's cars with extended service intervals.

### Характеристики

	Unit	Average Value
Плотность при 15 °C	kg/l	0.849
Вязкость при 40 °C	mm <sup>2</sup> /s	55.10
Вязкость при 100 °C	mm <sup>2</sup> /s	9.80
Вязкость при минус 35 °C	mPas	5920
Коэффициент вязкости		160
Температура вспышки по Кливленду	°C	230
Температура застывания	°C	-51
Общее щелочное число	mgKOH/g	6.2
Содержание сульфатной золы	%	0.54

### Упаковка



12x1L 4x4L 3x5L 20L 60L 210L IBC