



Cooler Master is releasing the Hyper 212 Spectrum V3, a redesigned addition to its popular 212 Spectrum predecessor. The 4 heat pipe array has been treated with silver nickel plating for unhindered heat conductivity as well as matching aesthetics. The cooler height is set at 152mm, allowing for a wide range of compatibility in most chassis without sacrificing cooling. The installation brackets give you the versatility for the latest platforms on market.

HYPER 212 SPECTRUM V3




Spectrum ARGB Fan

120mm Spectrum ARGB fan certified for compatibility with Asus Aura, ASRock RGB, GIGABYTE and MSI RGB Motherboards. (Controller not included)



Wide Range Compatibility

Compact 152mm height designed for wide chassis compatibility without sacrificing performance




Nickel Plated Heat Pipes

4 heat pipes with silver nickel plated finish provide exceptional cooling and aesthetics



Upgraded Installation Brackets

Redesigned brackets simplify installation on the latest available platforms



Direct Contact Technology

Direct Contact Technology maximizes contact surface area and heat exchange

Spectrum 120 ARGB Fan - 120mm Spectrum ARGB fan compatible with Asus Aura, ASRock RGB, GIGABYTE and MSI RGB Motherboards.

Upgraded Installation Brackets - Redesigned brackets simplify installation on the latest available platforms.
Nickel Plated Heat Pipes - 4 heat pipes with silver nickel plated finish provide exceptional cooling and aesthetics.
Wide Range Compatibility - Compact 152mm height designed for wide chassis compatibility without sacrificing performance.

Direct Contact Technology - Direct Contact Technology maximizes contact surface area and heat exchange.

SPECIFICATIONS

Product Name	Hyper 212 Spectrum V3		
Product Number	RR-S4NA-17PA-R1		
Exterior Color	Silver		
CPU Socket	Intel® LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 socket AMD® AM5 / AM4		
Dimensions (Lx W x H)	124 x 73 x 152 mm (4.8 x 2.8 x 5.9 inch)		
Heat Sink Material	4 Heat Pipes/ Aluminum Fins		
Fan			120mm Fan
	Dimensions (L x W x H)	120 x 120 x 25mm	
	Profile	Addressable RGB	
	Quantity (pcs)	1 PC	
	Speed	650 ~ 1750 RPM ± 10%	
	Airflow (Max)	122.2 m³/h (71.93 CFM)	
	Pressure (Max)	1.86 mmH ₂ O	
	MTTF	>160,000 Hours	
	Noise Level (Max)	27.2 dB(A)	
	Bearing	Rifle	
	Power Connector	4-Pin PWM	
	Rated Voltage	12 VDC	
	Rated Current	0.26 A	
	Safety Current	0.37 A	
	Power Consumption	3.12 W	
Warranty	2 years		

PACKING INFORMATION

EAN code	4719512132128
UPC code	884102104442
Net weight	0.65 kg
Gross weight	0.76 kg
Package dimension (L x W X H)	13.8 x 11 x 18.8 cm
Carton dimension (L x W x H)	57.5 x 29 x 21.5 cm
Units/CTN	10

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	5940	36	N/A
40'	11800	36	N/A
40 HQ	13200	40	N/A