

FAVORIT

Technical Data Sheet

Favorit Gear GL-4 SAE 80W-90 API GL-4



Packages:

1L, 4L, 20L, 60L, 208L

Meets the requirements and specifications:

SAE 80W-90 API GL-4

[EN] FAVORIT Gear GL-4 multipurpose multigrade mineral transmission oil for manual gearboxes, lock units and driving axle functioning at medium and high loads. Provides perfect lubrication and anti-corrosion protection.

[RU] FAVORIT Gear GL-4 всепогодное универсальное трансмиссионное масло на минеральной основе, предназначенное для смазки механических коробок передач, синхронизаторов, ведущих мостов, работающих при умеренных и высоких нагрузках. Обеспечивает надежную смазку и отличную противокоррозионную защиту.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	161,08
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	15,92
Viscosity index	STB 1797	101,67
Flash poin, °C	GOST 4333	214
Pour point, °C	GOST 20287	-20
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m ³	GOST 3900	885

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.