

FAVORIT

Technical Data Sheet

Favorit Formel Super 10W-40



Packages:
5L, 20L, 60L, 208L

[EN] Favorit Formel Super 10W-40 designed for all types of gasoline and diesel engines. They contain a multipurpose additive package that provides optimum antiwear and antioxidant properties of the oil. They guarantee reliable lubrication at high temperatures and the cleanliness of engine parts.

[RU] Favorit Formel Super 10W-40 предназначено для всех типов бензиновых и дизельных двигателей. Содержит универсальный пакет присадок, обеспечивающий оптимальные противоизносные и антиокислительные свойства масла. Гарантирует надежное смазывание при высоких температурах и чистоту деталей двигателя.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104	12,31
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104	81,53
Viscosity index	STB 1797	147
Flash point, °C	GOST 4333	230
Pour point, °C	GOST 20287	-28
TBN, g KOH/kg	GOST 11362	7,0
Density at 20°C, kg/m ³	GOST 3900	863,7

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.