



USER MANUAL



MADE IN PRC
specially for AMP™



AMPGROUP.PRO

 Your AMP™ product was developed and manufactured with high-quality materials and components which can be recycled and/or re-used. This symbol indicates that electrical and electronic equipment must be disposed of separately from normal garbage at the end of its operational lifetime. Please dispose of this product by bringing it to your local collection point or recycling centre for such equipment. This will help to protect the environment in which we all live.

Full-range Speaker

PROMO
series

We respect your choice for choosing AMP™.
AMP™ company does everything possible
to ensure that our products meet your needs,
and quality match the best world standards.

WE RESPECT YOUR CHOICE!

Congratulations on your purchase of a AMP™ Acoustics. It has been designed, engineered and manufactured to bring you the highest level of performance and quality, and will afford you of listening pleasure. AMP™ — ENERGY OF SOUND!

Specifications	FR40 V3	FR52 V3	FR65 V3	FR80 V3	FR69 V3
Type	Full-range	Full-range	Full-range	Full-range	Full-range
Diameter / Dimension	4" (100 mm)	5" (130 mm)	6.5" (165 mm)	8" (200 mm)	6x9" (150x230 mm)
Impedance	3 Ω	3 Ω	3 Ω	3 Ω	3 Ω
Nom. power	30 W	35 W	40 W	55 W	50 W
Sensitivity	90 dB	91 dB	93 dB	92 dB	93 dB
Frequency response	100 Hz – 15 kHz	90 Hz – 15 kHz	75 Hz – 15 kHz	60 Hz – 15 kHz	60 Hz – 15 kHz
Magnet	Ø70x10 mm Y30	Ø70x10 mm Y30	Ø80x10 mm Y30	Ø90x15 mm Y30	Ø90x15 mm Y30
Voice coil diameter	1" (25 mm) KSV	1" (25 mm) KSV	1" (25 mm) KSV	1" (25 mm) KSV	1" (25 mm) KSV
Woofer cone	Pressed paper				
Speaker basket	Steel	Steel	Steel	Steel	Steel

All specifications subject to change without notice.

РУС.

МЫ ЦЕНИМ ВАШ ВЫБОР!

Поздравляем вас с покупкой автомобильной акустики AMP™. AMP™ — это продукция высочайшего уровня производительности и качества. AMP™ — ЭНЕРГИЯ ЗВУКА!

Характеристики	FR40 V3	FR52 V3	FR65 V3	FR80 V3	FR69 V3
Тип	Full-range	Full-range	Full-range	Full-range	Full-range
Диаметр / Размер	4" (100 мм)	5" (130 мм)	6.5" (165 мм)	8" (200 мм)	6x9" (150x230 мм)
Сопротивление	3 Ω	3 Ω	3 Ω	3 Ω	3 Ω
Мощность ном.	30 Вт	35 Вт	40 Вт	55 Вт	50 Вт
Чувствительность	90 дБ	91 дБ	93 дБ	92 дБ	93 дБ
Диапазон частот	100 Гц – 15 кГц	90 Гц – 15 кГц	75 Гц – 15 кГц	60 Гц – 15 кГц	60 Гц – 15 кГц
Магнит	Ø70x10 мм Y30	Ø70x10 мм Y30	Ø80x10 мм Y30	Ø90x15 мм Y30	Ø90x15 мм Y30
Звуковая катушка	1" (25 мм) KSV	1" (25 мм) KSV	1" (25 мм) KSV	1" (25 мм) KSV	1" (25 мм) KSV
Материал диффузора	Бумага прессованная				
Материал корзины	Сталь	Сталь	Сталь	Сталь	Сталь

Производитель оставляет за собой право, без предварительного уведомления, вносить изменения в конструкцию изделия, не ухудшающие его потребительских свойств, с целью улучшения его технических характеристик.

Wiring / Подключение



Be sure to observe polarity to avoid audio phase problems.



При подключении к головному устройству или усилителю соблюдайте полярность.

INFORMATION ABOUT WARRANTY REPAIR

Service center

Work performed

Date

Service center

Work performed

Date

Warranty period	12 months	Гарантийный срок эксплуатации	12 месяцев
Warranty period of storage	3 years	Гарантийный срок хранения	3 года
Warranty service life	5 years	Гарантийный срок службы	5 лет
The operating temperature	+5...+30°C	Рабочая Т окружающего воздуха	+5...+30°C
Transportation and storage temperature	-40...+40°C	Т транспортирования и хранения	-40...+40°C

ГАРАНТИЙНЫЕ РАБОТЫ

Stamp

Stamp